



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720

ADVANCE SKID STEER / BACKHOE CATEGORY



ADVANCE

[View Advance R-4E Series Tires](#)



Features & Benefits

- Wide tread design to decrease soil compaction.
- Puncture resistant tread design.
- Deep tread pattern to provide additional traction.
- Wear resistant compound to prolong tire service life.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4E	96226G	340/80R18 TL R-4E(143A8)	TL	13.5	39.4	58	6010	35.3	114.4
R-4E	96228G	280/80R20	TL	11.1	37.6	58	4540	32.7	85
R-4E	96230G	340/80R20	TL	13.5	41.4	58	6150	35.2	117
R-4E	96232G	400/70R20	TL	15.9	42	58	7150	30.7	135
R-4E	96200G	17.5LR24	TBLS	17.5	49.2	46	7820	45.4	197
R-4E	96202G	17.5L(460/70)R24 STEEL BELT	TL	17.9	49.4	58	9650	45.4	207.9
R-4E	96206G	19.5LR24	TBLS	19.5	52	44	8820	47.9	248

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4E	96205G	19.5LR24	TBLS	19.5	52	44	8820	47.9	240
R-4E	96208G	540/70424	TBLS	21.7	53.8	35	8050	49.8	288
R-4E	96210G	540/70(21L)R24 STEEL BELT	TL	21.7	53.8	46	10200	49.8	297.3
R-4E	96212G	400(15.5)/80R24 STEEL BELT	TL	15.9	49.2	58	8800	44.1	190
R-4E	96215G	400(15.5)/80R24 STEEL BELT	TL	15.9	49.2	73	10500	44.1	197.1
R-4E	96217G	400(405)/70R24 STEEL BELT	TL	15.9	46.1	58	7850	38.4	168.7
R-4E	96218G	400(405)/70R24 STEEL BELT	TL	15.9	46.1	73	9350	38.4	175.9
R-4E	96216G	400/70R24 STEEL BELT	TL	15.9	46.1	46	6400	38.4	177.6
R-4E	96220G	440/80(16.9)R24 STEEL BELT	TL	17.4	51.7	58	10200	46.6	224.9
R-4E	96222G	480/80(18.4)R26 STEEL BELT	TL	18.9	56.2	46	9900	47.9	280.6
R-4E	96224G	440/80(16.9)R28 STEEL BELT	TL	17.4	55.7	46	8800	47.9	251.3

[View Advance R-4B Series Tires](#)

Features & Benefits

- Provides tight center bars for excellent road-ability.
- Reinforced sidewall with curb and rim guard to provide extra protection against rim and sidewall damage.
- Deep tread lugs deliver excellent traction in muddy soil conditions.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4B	99110G	16.9-24/12	TBLS	16.9	51.5	38	7165	35.3	191.68
R-4B	99120G	17.5L-24/12	TBLS	17.5	48.9	38	6605	32	163.25
R-4B	99130G	19.5L-24/12	TBLS	19.5	51.7	33	7605	35.9	187.87
R-4B	99140G	21L-24/12	TBLS	21	54.3	32	8545	36.5	233.47

[View Advance R-4A Series Tires](#)



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720



Features & Benefits

- Premium - Ultimate backhoe tire.
- Extra wide tread design for high flotation and super stability in extreme conditions.
- Large center bars for superior road-ability, extra deep tread for superior traction.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4A	99030HG	19.5L-24/14	TBLS	19.5	51.7	38	8145	35.9	214.92
R-4A	99040HG	21L-24/16	TBLS	21	54.3	41	9920	40.1	242.47

[View Advance R-4 Series Tires](#)



Features & Benefits

- Wide foot print for high flotation and stability, delivers excellent traction.
- Premium tread width and depth provides increased tire life and trouble-free performance.
- Economy

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4	99160G	14.9-24/12	TBLS	14.9	48.9	42	6395	32	153.45
R-4	98010LG	16.9-24/12	TBLS	16.9	51.5	35	5465	32.8	162.52
R-4	98020LG	17.5L-24/12	TBLS	17.5	48.9	33	4255	33.4	154.25
R-4	98030LG	19.5L-24/12	TL	19.5	51.7	33	7605	37.2	
R-4	98040LG	21L-24/12	TBLS	21	54.3	28/*28	5310/*5840	37.2	233.47



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720

[View Advance R-4D Series Tires](#)



Features & Benefits

- Durable tread pattern for high flotation and super stability.
- Designed against resistance to chunking and tearing.
- Deep tread lugs deliver excellent traction in muddy soil conditions.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4D	98075G	18.4-26/12	TBLS	18.4	56.1	33/*32	6580/*5840	36.5	225.32
R-4D	98070G	16.9-28-12	TBLS	16.9	55.5	35	5840	35.3	183.3
R-4D	98072G	16.9-28-14	TBLS	16.9	55.5	41	6615	35.3	196.53

[View Advance R-4 IND Series Tires](#)



Features & Benefits

- Bar angle provides superior traction off road and good wear during road transportation.
- Heavy duty design for excellent ride, snag resistance and long wear.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4 IND	99215G	340(12.5)/80-18-12	TL	13.5	39.4	58	6005	34.6	101
R-4 IND	99220G	340(12.5)/80-20-12	TL	13.5	41.4	58	6175	34.6	111
R-4 IND	99210G	400/70-20-14	TL	15.9	42	58	7165	40.3	138
R-4 IND	99205G	480/80-26 -14	TL	18.9	56.2	35	7850	42.8	236
R-4 IND	99200G	440/80-28-14	TL	17.4	55.7	35	6950	42.8	229



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720

[View Advance F-3 Series Tires](#)



Features & Benefits

- Applicable for agricultural tractors in industrial service and backhoes.
- Deep tread offers excellent impact, cut and puncture resistance.
- Provides superior traction on hard soil, asphalt and concrete.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
F-3	19501G	11L-15/10	TBLS 11		32	52	2340	16	55.92
F-3	19502G	11L-15/14	TBLS 11		32	73	2855	16	61.13
F-3	19520G	11L-16/10	TBLS 11		33	52	2470	16	59.55
F-3	19521G	11L-16/14	TBLS 11		33	73	3055	16	62.44

[View Advance GLR05 Series Tires](#)



Features & Benefits

- All Steel radial casing
- Extremely strong sidewall strength
- Increased tread wear on abrasive surfaces

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
GLR05	42500G	10R16.5	TBLS 10.4		30.3	55	3970	30.2	76
GLR05	42505G	12R16.5	TBLS 12		32.7	55	5680	34	100

[View Advance GLR25 Series Tires](#)



Features & Benefits

- Reinforces radial construction provides better traction and smoother ride than bias tires.
- All-steel construction provides superior puncture resistance and longer life.
- Incredible traction in slippery, muddy terrain.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
GLR25	42510G	10R16.5 (265/70R16.5)	TL		30.1	55	3970	24.6	74
GLR25	42515G	12R16.5 (305/70R16.5)	TL		32.7	55	5680	29	96

[View Advance L-2B Series Tires](#)



Features & Benefits

- Ultra heavy duty skid-steer tire.
- Triple step lug provides self cleaning capabilities.
- Extra deep tread for superior traction and longer tread life.
- Rim guard

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
L-2B	16000G	5.70x12/8	TBLS	5.7	22.4	90	1875	18.9	17.38
L-2B	16002G	23X8.50-12/8	TBLS	8.4	22.6	65	2170	18.9	24.64
L-2B	16004G	27X8.50-15/10	TBLS	8.4	25.9	70	2270	18.9	31.9



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720

[View Advance LD180 Series Tires](#)



Features & Benefits

- Robust, reinforced tread lug provides superior traction.
- Advanced compound resists tears and punctures.
- Reinforced sidewall for extra durability.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
LD180	16070G	18x8.50-10NHS	TL	7.5	18.5	22	825	16.4	13.2

[View Advance L-2E Series Tires](#)



Features & Benefits

- Ultra heavy duty skid-steer tire.
- Features reinforced sidewalls and rim guard that provides extra protection against sidewall damage.
- Extra deep tread for superior traction and longer tread life.
- Rim guard

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
L-2E	16050G	10-16.5/8	TBLS	10.4	31.4	59	4140	21.4	54.55
L-2E	16054G	10-16.5/10	TBLS	10.4	31.4	75	4710	21.4	55.28
L-2E	16028G	10-16.5/12	TBLS	10.4	31.4	90	5240	21.4	61.36
L-2E	16030G	10-16.5/14	TBLS	10.4	31.4	104	6040	21.4	62.52
L-2E	16038G	12-16.5/14	TBLS	12.36	33.3	90	6780	26.5	82.62
L-2E	16040G	12-16.5/16	TBLS	12.36	33.3	110	7920	26.5	87.01

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
L-2E	16042G	33X15.50-16.5/12	TBLS	15.5	33	61	8005	32.1	95.9

[View Advance L-2D Series Tires](#)



Features & Benefits

- Durable tread pattern for high flotation and super stability.
- Designed against resistance to chunking and tearing.
- Features also included rim guard and heavy duty sidewall.
- Economy

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
L-2D	16051G	10-16.5/8	TBLS	10.4	30.4	59	4140	20.2	41.95
L-2D	16052G	10-16.5/10	TBLS	10.4	30.4	75	4710	20.2	43.16
L-2D	16055G	12-16.5/10	TBLS	11.18	33.1	65	5600	23.9	52.16
L-2D	16056G	12-16.5/12	TBLS	11.18	33.1	80	6320	23.9	53.57
L-2D	16058G	14-17.5/16	TBLS	13.7	36.3	100	8260	27.7	101.91
L-2D	16059G	15-19.5/16	TBLS	15.3	40.1	80	10880	31.5	127.97
L-2D	19532G	10.5/80-18/12	TBLS	10.8	34.7	62	3230	20.2	59.44

[View Advance L-4A Series Tires](#)



Features & Benefits

- Severe service skid-steer tire with non-directional design for packed soil, or hard surface applications.

- Reinforced sidewall with curb and rib guard that provides extra protection against rim and sidewall damage.
- Reinforced for superior tread stability and greater penetration resistance.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
L-4A	16150G	10-16.5/10	TBLS	10.4	30.4	75	4710	34	71.63
L-4A	16152G	10-16.5/12	TBLS	10.4	30.4	90	5240	34	71.59
L-4A	16160G	12-16.5/12	TBLS	12.1	32.7	80	6320	42.2	97.55
L-4A	16162G	12-16.5/14	TBLS	12.1	32.7	90	6780	42.2	99.93
L-4A	16170G	14-17.5/16	TBLS	13.7	36.3	100	8260	47.2	148.63
L-4A	16180G	15-19.5/14	TBLS	15.3	40.1	70	10060	47.2	170.04
L-4A	16182G	12-16.5/14	TBLS	12.1	32.7	90	6780	42.2	112.13
L-4A	16151G	10-16.5/10	TBLS	10.4	30.4	75	4710	34	68.13
L-4A	16153G	10-16.5/12	TBLS	10.4	30.4	90	5240	34	68.45
L-4A	16164G	12-16.5/12	TBLS	12.1	32.7	80	6320	42.2	94.28
L-4A	16163G	12-16.5/14	TBLS	12.1	32.7	90	6780	42.2	95.64
L-4A	16171G	14-17.5/16	TBLS	13.7	36.3	100	8260	47.2	148.63
L-4A	16174G	15-19.5/14	TBLS	15.3	40.1	70	10060	47.2	165.26

[View Advance L-5 Series Tires](#)



Features & Benefits

- Extra deep tread provides excellent rock type damage resistance and long tread life.
- Open non-directional tread pattern provides all around traction with excellent self cleaning.
- Solid center line section provides long wear, smooth ride and is ideal for high torque applications and hard rock quarry service.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
L-5	16190G	32X11-16.5/10	TBLS	12.1	32.7	60	5340	48.5	106
L-5	16195G	34X12.5-16.5/12	TBLS	12.1	34.3	65	5600	52	119.7

[View Advance R-4C Series Tires](#)



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720



Features & Benefits

- Durable tread pattern for high flotation and super stability.
- Designed against resistance to chunking and tearing.
- Features also include rim guard and heavy duty sidewall.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4C	19530G	10.5/80-18/14	TBLS	10.8	34.7	70	3375	32	77.84
R-4C	19534G	12.5/80-18/16	TBLS	12.1	37.9	71	4805	32	115.43
R-4C	19536G	10-16.5/12	TBLS	10.4	30.4	90	5240	21.4	61.38
R-4C	19537G	12-16.5/14	TBLS	12.1	32.7	90	6780	26.5	86.33

[View Advance I-3D Series Tires](#)



Features & Benefits

- Moderate traction tread, drive wheel.
- Backhoe use.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-3D	59010G	31x15.50-15/12	TBLS	15.4	31.2	75	3705	26.5	74.8
I-3D	59020G	26x12-12/10	TBLS	12.1	25.5	65	3595	22.7	37.71

[View Advance I-3C Series Tires](#)



Features & Benefits

- Light traction tread, drive wheel.
- Backhoe use.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-3C	47025G	550/60-22.5/16	TBLS	21.1	49.4	44	*11670/**8260	31.5	207
I-3C	47028G	600/55-22.5/16	TBLS	23.6	48.2	37.7	7590	32.8	227.37
I-3C	47020G	400/60-15.5/14	TL	15.9	34.4	52	*7165/**4410	25.2	76
I-3C	47022G	500/60-22.5/16	TL	19.8	46.2	71	*13200/**9350	32.8	227
I-3C	47026G	600/50-22.5/16	TL	24.1	46.1	46	*12300/**8810	32.8	254
I-3C	47030G	700/50-22.5/12	TBLS	27.6	50	32	*12330/**8810	34	345.82
I-3C	47032G	700/50-26.5/16	TL	28	52.5	35	*12800/**9100	32.8	334
I-3C	59025G	16.5L-16.1/10	TBLS	16.5	41.2	40	5680	29	116

[View Advance I-3 Series Tires](#)



Features & Benefits

- Deep tread for excellent traction and self-cleaning.
- Strong nylon carcass for stability and durability.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-3	93050G	10.5/80-18/12	TL	10.8	35.7	62	*4850/**3420	25.2	58
I-3	93054G	12.5/80-18/12	TL	12.1	38.9	54	*5840/**4080	25.2	88

[View Advance I-3A Series Tires](#)



Features & Benefits

- Deep tread for excellent traction and self-cleaning.
- Strong nylon carcass for stability and durability.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-3A	93058G	15.5/80-24/12	TL	15.6	49.7	44	*9090/**6390	44.1	172

[View Advance I-3F Series Tires](#)



Features & Benefits

- Unique traction designed for many agricultural applications
- Engineered for on and off road services in any weather

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-3F	93066G	10.0/75-15.3/12	TL	10.4	30.7	68	3750	27.1	43
I-3F	93068G	11.5/80-15.3/10	TL	11.4	34.1	49	3000	18.9	55
I-3F	93070G	11.5/80-15.3/14	TL	11.4	34.1	69	3750	18.9	57

SKU: category-advance-farm-skid-steer-backhoe



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720