

SAMSON FARM CATEGORY


SAMSON

[View Samson AR1200 Series Tires](#)

Features & Benefits

- Non directional tread pattern provides excellent traction, increased wear, and allows for greater mounting versatility.
- Low-profile sidewall ensures excellent stability in highlifting operations.
- Specially designed sidewall provides added cut-and-puncture sidewall protection.
- L-3 Industry Designation.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
AR1200	AR120019-2	200/70R16 (94D)	TL	7.755905512	27.00787402	35	1480	40.31496063	
AR1200	AR120020-2	240/70R16 (104D)	TL	9.606299213	29.21259843	35	1980	45.35433071	
AR1200	AR120021-2	260/70R16 (109D)	TL	10.15748031	30.31496063	35	2270	46.61417323	



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
AR1200	AR120024-2	280/70R16 (112D)	TL	11.1023622	31.41732283	35	2464	47.87401575	
AR1200	AR120025-2	300/70R16 (106D)	TL	11.61417323	32.51968504	23	2090	49.13385827	
AR1200	AR120022-2	260/70R20 (113D)	TL	10.15748031	34.33070866	35	2530	46.61417323	
AR1200	AR120045-2	320/85R20 (119D)	TL	12.55905512	41.41732283	23	3000	55.43307087	
AR1200	AR120044-2	380/85R24 (131D)	TL	14.96062992	49.4488189	23	4290	57.95275591	
AR1200	AR120049-2	420/85R24 (137D)	TL	16.45669291	52.12598425	23	5080	62.99212598	
AR1200	AR120002-2	480/65R28 (142D)	TL	18.85826772	52.55905512	35	5840	61.73228346	
AR1200	AR120004-2	540/65R28 (149D)	TL	21.65354331	55.62992126	35	7150	65.51181102	
AR1200	AR120010-2	600/65R28 (147D)	TL	23.26771654	58.7007874	23	6765	69.29133858	
AR1200	AR120011-2	600/65R28 (154D)	TL	23.26771654	58.7007874	35	8250	76.8503937	
AR1200	AR120052-2	420/85R28 (144D)	TL	16.45669291	56.1023622	35	6150	62.99212598	
AR1200	AR120006-2	540/65R30 (150D)	TL	21.65354331	57.63779528	35	7400	65.51181102	
AR1200	AR120056-2	420/85R30 (140D)	TL	16.45669291	58.11023622	23	5500	62.99212598	
AR1200	AR120008-2	540/65R34 (152D)	TL	21.65354331	61.65354331	35	7810	65.51181102	
AR1200	AR120013-2	650/65R38 (163D)	TL	25.39370079	71.2992126	35	10700	76.8503937	
AR1200	AR120023-2	520/70R38 (150D)	TL	20.31496063	68.85826772	23	7400	68.03149606	
AR1200	AR120032-2	710/70R38 (171D)	TL	28.18897638	77.12598425	35	13530	73.07086614	
AR1200	AR120042-2	340/85R38 (133D)	TL	13.5	60.8	23	4530	56.7	
AR1200	AR120059-2	460/85R38 (149D)	TL	17.91338583	68.77952756	23	7150	64.2519685	
AR1200	AR120061-2	520/85R38 (155D)	TL	20.31496063	72.79527559	23	8550	68.03149606	
AR1200	AR120070-2	650/85R38 (173D)	TL	25.39370079	81.53543307	35	14300	76.8503937	
AR1200	AR120015-2	650/65R42 (165D)	TL	25.39370079	75.31496063	35	11400	76.8503937	
AR1200	AR120034-2	480/80R42 (151D)	TL	18.85826772	72.24409449	23	7590	70.5511811	
AR1200	AR120064-2	520/85R42 (157D)	TL	20.31496063	76.81102362	23	9100	68.03149606	
AR1200	AR120001-2	520/85R46 (164D)	TL	20.31496063	80.78740157	35	11000	68.03149606	

[View Samson AR1000 Series Tires](#)



Features & Benefits

- 45° bar angle and extremely deep bars provide superior traction in the field.
- Heavy duty design for snag resistance and long wear.
- Flexible sidewall creates large square footprint which decreases soil compaction.



Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
AR1000	96400-2	280/70R18	TL	11.1	33.4	35	2600	46.6	67
AR1000	96402-2	280/70R20	TL	11.1	35.4	35	2760	46.6	73
AR1000	96404-2	320/70R20	TL	12.5	38.6	23	2540	48.5	90
AR1000	96406-2	360/70R20	TL	14	41	35	4080	49.1	111
AR1000	96116-2	380/70R20	TL	15	42.6	35	4400	50.4	123
AR1000	96112-2	280/85R20	TL	11.1	38.7	23	2470	50.4	87
AR1000	96131-2	440/65R24	TL	17.4	46.5	35	4800	58	300
AR1000	96137-2	540/65R24	TL	21.7	51.7	35	6600	63	114.3
AR1000	96123-2	320/70R24	TL	12.6	43.1	23	2760	49.1	132
AR1000	96129-2	360/70R24	TL	14.1	45.4	35	3860	51	142
AR1000	96133-2	380/70R24	TL	15	46.9	23	3640	52.9	192
AR1000	96171-2	420/70R24	TBLS	16.5	49.1	35	4940	56.7	173.8
AR1000	96118-2	280/85R24	TL	11.1	42.8	23	2676	54.2	108
AR1000	96122-2	320/85R24	TL	12.6	45.4	23	3300	55.4	135
AR1000	96162-2	340/85R24	TL	13.5	46.8	23	3640	56.7	140
AR1000	96152-2	380/85R24	TL	14.9	49.5	23	4300	58	171
AR1000	96126-2	420/85R24	TL	16.5	52.1	23	5080	60.5	201
AR1000	96127-2	14.9R26	TL	14.9	51.8	23	3860	59.2	170
AR1000	96128-2	14.9R26	TL	14.9	51.8	30	4400	59.2	170
AR1000	96408-2	750/65R26CFO	TL	29.7	64.4	46	13530	70.6	590
AR1000	96136-2	620/75R26(23.1R26)	TL	24.6	62.6	46	11700	69.3	484.5
AR1000	96111-2	440/65R28	Tubless	17.4	50.5	35	5200	56.7	402
AR1000	96148-2	540/65R28	TL	21.7	55.6	23	5840	63	304
AR1000	96121-2	600/65R28	TBLS	23.3	58.7	35	8250	64.3	377
AR1000	96107-2	320/70R28	Tubless	12.6	46.8	23	3000	51.7	146
AR1000	96108-2	360/70R28	Tubless	14.1	49.3	34.8	4180	52.9	168
AR1000	96109-2	380/70R28	Tubless	15	50.9	35	4540	55.4	223
AR1000	96168-2	420/70R28	TL	16.5	53.1	23	4540	56.7	181
AR1000	96146-2	480/70R28	TL	18.9	55.9	23	5520	59.2	263
AR1000	96138-2	320/85R28	TL	12.6	49.4	23	3520	55.4	146.5
AR1000	96164-2	340/85R28	TL	13.5	50.9	23	3860	56.7	161
AR1000	96140-2	380/85R28	TL	15	53.4	23	4540	58	192
AR1000	96101-2	420/85R28	TBLS	16.5	56.1	35	6160	60.5	232.3
AR1000	96110-2	14.9R30	Tubless	14.9	55.1	23	4070	58	200
AR1000	96153-2	540/65R30	TL	21.7	57.6	23	6000	63	314
AR1000	96154-2	540/65R30	TL	21.7	57.6	35	7400	63	339
AR1000	96166-2	480/70R30	TL	18.9	58.2	23	5680	59.2	277
AR1000	96132-2	380/85R30	TL	15	55.4	23	4800	59.2	198
AR1000	96100-2	420/85R30	Tubless	16.5	58.1	23	5510	60	232
AR1000	96172-2	460/85R30	TL	17.9	60.8	23	6400	65.5	328
AR1000	96160-2	420/90R30	TL	16.5	59.8	23	6800	60.5	274
AR1000	96155-2	IF600/70R30	TL	23.7	63.1	23	9650	68	121
AR1000	96158-2	900/60R32	TL	35.3	74.5	46	18200	76.9	876
AR1000	96156-2	800/65R32	TL	31.4	73	23	12000	75.6	753
AR1000	96176-2	540/65R34	TL	21.7	61.7	23	6400	63	345.7



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
AR1000	96139-2	620/75R34	TL	24.6	70.6	46	13200	60.4	559
AR1000	96151-2	380/85R34	TBLS	15	59.5	35	5840	59.2	252.5
AR1000	96175-2	420/85R34	TBLS	16.5	62.1	35	6800	60.5	267
AR1000	96179-2	460/85R34	TL	17.9	64.8	23	6800	65.5	344
AR1000	96193-2	IF580/80R34	TL	22.6	70.5	52	16100	69.2	538
AR1000	96178-2	15.5R38	TL	15.5	61.8	23	4680	44.1	244.7
AR1000	96114-2	540/65R38	Tubless	21.7	65.6	35	8050	63	512
AR1000	96184-2	600/65R38	TL	23.3	68.7	23	8050	64.3	536
AR1000	96185-2	650/65R38	TL	25.4	71.3	23	9100	66.8	700
AR1000	96182-2	580/70R38	TL	22.7	71.9	23	8550	66.8	435
AR1000	96117-2	620/70R38	Tubless	24.6	72.2	46.4	13200	65.5	737
AR1000	96125-2	710/70R38	Tubless	28.2	77.1	23	11700	73.1	656
AR1000	96124-2	710/70R38	TL	28.2	77.1	35	13560	73.1	514
AR1000	96188-2	IF800/70R38	TL	31.3	82.1	23	17100	75.6	764.3
AR1000	96134-2	480/80R38	TBLS	18.9	68.2	35	7600	63	497
AR1000	96180-2	420/85R38	TL	16.5	66.1	23	6170	60.5	284.4
AR1000	96104-2	520/85R38	Tubless	20.3	72.8	23	9100	68	441
AR1000	96103-2	520/85R38 (20.8R38)	TL	20.3	72.8	52	12800	68	485
AR1000	96119-2	650/85R38	Tubless	25.4	81.5	35	14300	76.9	251
AR1000	96115-2	18.4R42	Tubless	18.4	72.8	23	6940	65.5	378
AR1000	96189-2	600/65R42	TL	23.3	72.7	23	8250	64.3	572
AR1000	96191-2	650/65R42	TL	25.4	75.3	23	9350	66.8	592.7
AR1000	96190-2	650/65R42	TL	25.4	75.3	35	11400	66.8	240
AR1000	96145-2	620/70R42	TL	24.6	76.2	23	9900	65.5	533
AR1000	96144-2	620/70R42	TL	24.6	76.2	46	13900	65.5	569.4
AR1000	96192-2	IF710/70R42	TL	28.2	81.1	35	17100	75.6	436
AR1000	96130-2	480/80R42	TL	18.9	72.2	23	7600	65.5	411
AR1000	96105-2	520/85R42	Tubless	20.3	76.8	23	9090	68	472
AR1000	96106-2	520/85R42(20.8R42)	TL	20.3	76.8	35	10500	68	456
AR1000	96198-2	IF520/85R42	TL	20.7	76.8	35	12800	68	525
AR1000	96196-2	480/80R46	TL	18.9	76.2	23	7850	65.5	455
AR1000	96197-2	480/80R46	TL	18.9	76.2	35	9350	65.5	816.6
AR1000	96194-2	320/90R46	TL	12.6	68.7	52	6950	50.4	371
AR1000	96195-2	380/90R46	TL	15	72.9	35	7150	60.5	433
AR1000	96183-2	480/80R50	Tubless	18.9	80.2	23	8250	65.5	269
AR1000	96181-2	320/90R50	Tubless	12.6	72.7	52	7400	50.4	474
AR1000	96186-2	320/90R54	Tubless	12.6	76.7	52	7600	50.4	108

[View Samson AR100 Series Tires](#)



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720



Features & Benefits

- Economical Radial Rear Option
- Wide footprint reduces soil compaction
- Comfortable ride while roading
- Excellent puncture and tear resistant compound

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
AR100	96333-2	9.5R24	TL	9.5	40.9	30	2464	41.6	79
AR100	96335-2	12.4R24	TL	12.4	45	23	2992	45	115
AR100	96337-2	13.6R24	TL	13.6	47.6	30	3520	46.6	133
AR100	96310-2	14.9R24 TL AR100(R-1) 126A8	TBLS	14.9	49	23	3740	47.9	143.88
AR100	96312-2	14.9R24 TL AR100(R-1) 130A8	TBLS	14.9	49	35	4180	47.9	143.88
AR100	96330-2	15R24 TL AR100(R-1)144 A6	TBLS	16	52	40	6160	39.1	176
AR100	96331-2	15R24 TL AR100(R-1)148A6	TBLS	16.1	52	47	6930	39.1	176
AR100	96300-2	14.9R26 TL AR100(R-1) 127A8	TBLS	14.9	52	23	3850	47.9	151.58
AR100	96301-2	14.9R26 TL AR100(R-1) 132 A8	TBLS	14.9	52	30	4400	47.9	151.58
AR100	96339-2	11.2R28	TL	11.2	47.2	23	2750	44	108
AR100	96315-2	14.9R28 TL AR100(R-1)128A8	TBLS	14.9	53	23	3960	47.9	161.92
AR100	96316-2	14.9R28 TL AR100(R-1)133A8	TBLS	14.9	53	30	4532	47.9	161.92
AR100	96345-2	16.9R28	TL	16.9	55.9	30.5	5500	49.1	151.58
AR100	96344-2	14.9R30	TL	14.9	55.8	30.5	4664	47.9	151.58
AR100	96348-2	16.9R30	TL	16.9	58.1	23.2	5060	49.1	151.58
AR100	96340-2	18.4R30	TL	18.4	60.8	23	5830	52.9	259
AR100	96342-2	16.9R34	TL	16.9	62.4	30	5995	49	249
AR100	96320-2	18.4R34 TL AR100(R-1)144A8	TBLS	18.4	65	23	6160	51.7	278.08
AR100	96321-2	18.4R34 TL AR100(R-1)149 A8	TBLS	18.4	65	30	7150	51.7	278.08
AR100	96325-2	18.4R38 TL AR100(R-1) 146A8	TBLS	18.4	69	23	6600	51.7	300.74
AR100	96326-2	18.4R38 TL AR100(R-1) 151A8	TBLS	18.4	69	30	7590	51.7	300.74
AR100	96346-2	20.8R38	TL	20.8	72.2	23.2	8030	54.2	151.58
AR100	96347-2	20.8R38	TL	20.8	72.2	30.5	9075	54.2	151.58

[View Samson AR833 Series Tires](#)



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720



Features & Benefits

- A unique non-directional tire designed for performance on road and on agricultural/logging applications.
- High floatation tire to minimize soil compaction.
- Steel reinforced to resist punctures.
- Deep tread pattern to provide maximum traction and high flotation for field use.
- For use on articulated dump trucks, fertilizer trucks, spreaders, and farm trailers and tankers.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
AR833	66208-2	560/45R22.5 IMP	TBLS	21.4	42.4	58	7850/10725	30.2	206.3
AR833	66202-2	710/45R22.5 IMP	TBLS	28.6	47.7	58	11400/15180	31.5	324
AR833	66212-2	600/50R22.5	TL	24	46.1	58	9625	42.8	258.104
AR833	66206-2	560/60R22.5 IMP	TBLS	21.4	49	72	11400/15180	31.5	260
AR833	66200-2	710/50R26.5 IMP	TBLS	28.6	54.4	58	13200/18150	32.8	381.5
AR833	66204-2	600/55R26.5 IMP	TBLS	24	52.5	73	12760/17600	32.8	319.2
AR833	66210-2	650/55R26.5 IMP	TBLS	25.4	54.7	58	12800/17600	32.8	352.6
AR833	66214-2	750/60R30.5	TL	29.6	65.9	58	18150	32.7	482

[View Samson R-1S Series Tires](#)



Features & Benefits

- Bar angle provides superior traction in the field.
- Heavy duty design for snag resistance and long wear.
- Variety of sizes for use with tractors, and combines.
- Deeper tread. Long bar/short bar.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
-----------------------	-----	------	------	---------------	------------------	--------------------	----------	-------------	-------------



Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-1S	96005-2	6.00-16/6	TT	6.5	29.3	36	1090	34	28
R-1S	96007-2	6.50-16/6	TT	7.1	30.1	36	1245	34	31
R-1S	96008-2	7.50-16/8	TT	8	31.9	42	1650	32.8	36
R-1S	96009-2	7.50-16/8	TT	8.1	31.9	42	1655	34	35
R-1S	96003-2	9.5-20/8	TT TIRE ONLY	9.5	37.4	41	2105	41.6	47.83
R-1S	96002-2	8.3-24/8	TT TIRE ONLY	8.3	39.1	46	2115	37.8	48.97
R-1S	96004-2	9.5-24/8	TT TIRE ONLY	9.4	41.3	41	2445	41.6	59
R-1S	96000-2	11.2-24/6	TT TIRE ONLY	11.2	43.5	26/*26	2300/*2090	44	76.74
R-1S	96011-2	12.4-24/10	TT	12.4	45.7	40/*40	3520/*3200	46.6	101.83
R-1S	96012-2	13.6-24/8	TT	13.6	47.6	30/*28	3405/*3080	46.6	95
R-1S	96015-2	14.9-24/8	TT TIRE ONLY	15	49.8	26/*26	3880/*3520	47.9	132.04
R-1S	96016-2	16.9-24/8	TT	16.9	52.6	24/*24	4500/*4080	49.1	170
R-1S	96014-2	14.9-26/10	TT	14.9	51.8	33/*32	4530/*4080	47.9	131
R-1S	96017-2	18.4-26/10	TT TIRE ONLY	18.3	57.1	26/*26	5830/*5200	52.3	203.5
R-1S	96034-2	23.1-26/12	TT	23.2	63.2	24/*24	7960/*7150	53.7	346
R-1S	96021-2	9.5-28/8	TT	9.5	45.3	40	2675	41.6	89
R-1S	96040-2	11.2-28/6	TT	11.2	47.4	26/*26	2460/*2200	44.1	92
R-1S	96042-2	12.4-28/10	TT	12.4	49.6	41	3725	45.4	109
R-1S	96043-2	13.6-28/8	TT	13.6	51.6	30/*28	3625/*3300	46.6	121
R-1S	96020-2	14.9-28/8	TT TIRE ONLY	15	53.7	26/*26	4145/*3740	47.9	142.82
R-1S	96022-2	16.9-28/10	TT TIRE ONLY	16.9	56.5	29/*28	5245/*4680	49.1	173.21
R-1S	96044-2	18.4-28/10	TT	18.4	59	26/*26	5985/*5360	52.3	217
R-1S	96046-2	14.9-30/10	TT	14.9	55.7	33/*32	4830/*4300	47.9	149
R-1S	96048-2	16.9-30/12	TT	16.9	58.5	35/*33	6000/*5520	49.1	194
R-1S	96024-2	18.4-30/10	TT TIRE ONLY	18.3	61	26/*26	6205/*5520	52.3	223.3
R-1S	96050-2	23.1-30/12	TT	23.1	67.1	24/*24	8490/*7600	53.7	365
R-1S	96052-2	9.5-32/8	TT	9.4	49.2	41	2780	41.6	88
R-1S	96082-2	11-32/10	TT	12	53.5	35	3015	44.1	122
R-1S	96026-2	24.5-32/10	TT TIRE ONLY	24.6	71.1	20/*20	8710/*7850	54.2	372.9
R-1S	96054-2	16.9-34/10	TT	16.9	62.4	29/*28	5740/*5200	49.1	205
R-1S	96029-2	18.4-34/10	TT	18.3	65.2	26/*26	6590/*6000	52.3	242
R-1S	96056-2	12.4-36/12	TL	12.4	57.7	48	4685	45.4	153
R-1S	96058-2	11.2-38/12	TT	11.2	57.4	49	4155	44.1	128
R-1S	96070-2	6.50-16/6	TT	7.1	30.1	36	1245	34	31
R-1S	96063-2	15.5-38/8	TT	15.6	61.8	26	4080/*4540	46.6	188
R-1S	96060-2	16.9-38/10	TT	16.9	66.3	29	6085	49.1	237

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-1S	96030-2	18.4-38/10	TT TIRE ONLY	18.3	69.1	26/*26	6975/*6400	51.5	256.52
R-1S	96032-2	20.8-38/10	TT TIRE ONLY	20.9	72.2	23/*22	7660/*6950	52.9	320.32
R-1S	96065-2	18.4-42/10	TT	18.4	73.1	26	6600/*7340	51.5	325
R-1S	96062-2	20.8-42/12	TT	20.8	76.2	28/*26	8250/*8050	52.9	385
R-1S	96072-2	18.4-46/10	TL	18.4	77.1	26	6950	51.5	364
R-1S	96074-2	9.5-48/16	TT	9.5	65	57	3375	41.6	152
R-1S	96076-2	12.4-48/12	TT	12.4	69.3	46	6660	45.4	183
R-1S	96078-2	14.9-48/12	TT	14.9	73.8	39	8150	47.9	243
R-1S	96080-2	12.4-54/12	TL	12.4	75.6	45	7060	45.4	237

[View Samson R-1KA Series Tires](#)

Features & Benefits

- Bar angle provides superior traction in the field and good wear during road transportation.
- Excellent ride, snag resistance and long wear.
- Variety of sizes for use with tractors and combines.
- Heavy duty design.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-1KA	97000-2	11.2-24/4	TT TIRE ONLY	11.2	43.5	19/*18	1860/*1655	42.8	67.39
R-1KA	97001-2	11.2-24/8	TT TIRE ONLY	11.2	43.5	35	2700	42.8	73.17
R-1KA	97005-2	12.4-24/4	TT TIRE ONLY	12.4	45.7	16/*16	2085/*1870	41.6	81.27
R-1KA	97006-2	12.4-24/8	TT TIRE ONLY	12.4	49.6	33/*32	3120/*2830	41.6	86.64
R-1KA	97011-2	14.9-24/8	TT	15	49.8	26/*26	3880/*3520	45.4	132.04
R-1KA	97015-2	16.9-24/8	TT TIRE ONLY	16.9	52.6	24/*24	4500/*4080	49.9	172.61
R-1KA	97020-2	18.4-26/6	TT TIRE ONLY	18.3	57.1	16/*16	4385/*3960	49.9	191.62
R-1KA	97018-2	18.4-26/12	TT TIRE ONLY	18.3	57.1	33/*32	6580/*5840	49.9	207.57
R-1KA	97065-2	23.1-26/10	TT TIRE ONLY	23.2	63.2	20/*20	7155/*6400	52.9	298.34
R-1KA	97025-2	11.2-28/4	TT TIRE ONLY	11.2	47.4	19/*18	1980/*1760	44	77.07
R-1KA	97030-2	12.4-28/4	TT TIRE ONLY	12.4	49.6	16/*16	2215/*1980	41.6	90.6
R-1KA	97035-2	13.6-28/6	TT TIRE ONLY	13.6	51.6	23/*22	3155/*2830	46.6	131.78
R-1KA	97040-2	14.9-28/6	TT TIRE ONLY	15	53.7	20/*20	3550/*3200	47.9	149.12

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-1KA	97045-2	16.9-28/6	TT TIRE ONLY	16.9	56.5	19/*18	4055/*3640	49.1	179.21
R-1KA	97050-2	16.9-30/6	TT TIRE ONLY	16.9	58.5	19/*18	4190/*3740	49.1	177.74
R-1KA	97058-2	18.4-30/10	TT TIRE ONLY	18.3	61	26/*26	6205/*5520	49.9	201.54
R-1KA	97063-2	24.5-32/12	TT TIRE ONLY	24.6	71.1	24/*24	9680/*8800	54.2	370.24
R-1KA	97060-2	16.9-34/6	TT TIRE ONLY	16.9	62.4	19/*18	4440/*3960	49.1	195.62
R-1KA	97067-2	18.4-34/10	TT TIRE ONLY	18.3	65.2	26	6590	49.9	222.16
R-1KA	97075-2	15.5-38/8	TT TIRE ONLY	15.6	61.8	26	4540	46.6	174.75
R-1KA	97080-2	16.9-38/8	TT	16.9	66.3	24/*24	5555/*4940	49.1	206.73
R-1KA	97085-2	18.4-38/8	TT TIRE ONLY	18.3	69.1	20/*20	5985/*5360	49.9	235.18
R-1KA	97090-2	20.8-38/8	TT TIRE ONLY	20.9	72.2	19/*18	6810/*6150	52.9	296.27

[View Samson R-1 Series Tires](#)



Features & Benefits

- Bar angle provides superior traction in the field and good wear during road transportation.
- Variety of sizes for use with tractors, and combines.
- Heavy duty design for excellent ride, snag resistance and long wear.
- Economy version

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-1	97900-2	18.4-16.1		18.4	44.8	20	2910	25.2	120
R-1	97905-2	21.5L-16.1		21.5	46.4	36	7820	51.7	219
R-1	97003-2	9.5-20/5	TT TIRE ONLY	9.4	37.4	41	2105	37.8	47.83
R-1	97016-2	14.9-26/8	TBLS	14.9	51.8	26/*26	4010/*3640	45.4	135.92
R-1	97047-2	18.4-28/8	TT TIRE ONLY	18.4	59.1	20/*20	5090/*4680	46.6	134.82
R-1	97049-2	14.9-30/6	TBLS	14.9	55.7	20/*20	3670/*3300	47.9	162.84
R-1	97059-2	23.1-30/8	TT TIRE ONLY	23.1	67.1	16/*16	6690/*6000	46.6	269.48
R-1	97094-2	30.5L-32/16	TBLS	30.5	71.7	26	11000	56.7	548.94
R-1	97097-2	30.5L-32/16	TT	30.5	71.7	26	11000	56.7	481.83
R-1	97074-2	12-38/8	TT	13	62	20	3460	47.9	161.26

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-1	97088-2	18.4-42/10	TT	18.4	73.1	26/*26	7340/*6600	50.4	319.92

[View Samson R-1M Series Tires](#)



Features & Benefits

- Bar angle provides superior traction in the field and good wear during road transportation.
- Heavy duty design for excellent ride, snag resistance and long wear.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-1M	97013-2	15-24/8	TT TIRE ONLY	16.1	52.4	41	6170	44.1	144.98

[View Samson R-1T Series Tires](#)



Features & Benefits

- Deep lugs with center wide studs provide excellent traction and good self cleaning properties
- Special tread compound resists tears and punctures

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-1T	97600-2	6.00-12/6	TT	6.5	25.2	36	890	27.7	21
R-1T	97602-2	6.00-16/6	TT	6.5	29.3	36	1090	29	29
R-1T	97604-2	7.50-16/8	TT	8.1	31.9	42	1650	31.5	40



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-1T	97606-2	8.3-20/8	TT	8.3	35.2	43	1950	36.5	47

[View Samson R-1IG Series Tires](#)



Features & Benefits

- Bar angle provides superior traction in the field.
- Heavy duty design for snag resistance and long wear.
- Irrigation application.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-1IG	97017-2	14.9-24/6	TBLS	15	49.8	20/*20	3330/*3000	37.8	120.08
R-1IG	97412-2	14.9-24/6	TT	15	49.8	20	3410	37.8	92
R-1IG	97405-2	11.2-24	TT TIRE ONLY	11.22	43.5	18	1650	31.5	60
R-1IG	97406-2	11.2-24/6	TT TIRE ONLY	11.2	43.5	26	2090	31.5	65.12
R-1IG	97410-2	11.2-38	TT TIRE ONLY	11.18	57.44	18	2090	31.5	96
R-1IG	97411-2	11.2-38/6	TT TIRE ONLY	11.2	57.7	26	2530	31.5	95.88
R-1IG	97416-2	11.2-24	TL	11.2	42.1	26	2090	31.5	62
R-1IG	97418-2	11.2-38-6/6	TL	11.2	56.3	26	2535	31.5	95.26
R-1IG	97420-2	14.9-24-6/6	TL	14.9	49	20	3000	31.5	102.718

[View Samson IG100 Series Tires](#)



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720



Features & Benefits

- Wide footprint reduces soil compaction and increases wear.
- Unique rubber compound increase service life.

Individual Data Sheet SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
IG100	97425-2 11.2-24	TL	11.2	43.5	20	1980	32.8	77
IG100	97428-2 11.2-38	TL	11.2	57.7	30	3410	35.3	110
IG100	97430-2 14.9-24	TL	14.9	49.8	23	3630	39.1	119.9

[View Samson R-2 Series Tires](#)



Features & Benefits

- Wet traction drive wheel.
- Used in wet muck, rice, and cane farming.
- Deep Tread.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-2	97520-2	9.5-24	TT TIRE ONLY	9.5	42.3	30	1870	75.6	78
R-2	97502-2	14.9-24/8	TT TIRE ONLY	14.9	51.4	26/*26	3880/*3520	81.9	177.32
R-2	97515-2	14.9-28	TT TIRE ONLY	14.9	55.4	26	3740	81.9	200
R-2	97530-2	18.4-30	TT TIRE ONLY	18.4	63	32	6400	100.8	357
R-2	97514-2	18.4-34/10	TT	18.4	66.9	26/*26	6590/*6000	100.8	329.35

[View Samson R-3 Series Tires](#)



Features & Benefits

- Drive wheel with shallow tread.
- Minimal turf disturbance.
- Used on golf course work, light industrial service, and highway mowing.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-3	97302-2	9.5-24/4	TT	9.4	40.4	20/*20	1630/*1480	13.9	48
R-3	97312-2	14.9-24/8	TBLS	15.2	49.4	26/*26	3880/*3520	25.2	133.85
R-3	97314-2	16.9-28/12	TBLS	16.9	55.5	28	4680	26.5	188.01
R-3	97318-2	16.9-30/12	TBLS	16.9	57.5	32	5910	26.5	203.92

[View Samson R-3A Series Tires](#)



Features & Benefits

- Drive wheel with shallow tread.
- Minimal turf disturbance.
- Used on golf course work, light industrial service, and highway mowing.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-3A	97300-2	620/70-26/8	TT TIRE ONLY	24.6	59.2	16	5680	20.2	299.57



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720

[View Samson F-2 Series Tires](#)



Features & Benefits

- Wide foot print and more surface contact allows for even better steering control and resistance to side slip.
- Designed to resist stubble punctures.
- Self cleaning tread design enhanced steering performance.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
F-2	97100-2	4.00-12/4	TT TIRE ONLY	4.4	21.2	52	495	15.1	10.01
F-2	97105-2	5.00-12/4	TT TIRE ONLY	5.1	22.4	52	605	15.1	11.37
F-2	97139-2	4.00-15/4	TT	4.4	24.3	52	583	15.1	12
F-2	97120-2	5.00-15/4	TT TIRE ONLY	5.1	26.1	44	715	16.4	15.42
F-2	97125-2	7.5L-15/6	TT TIRE ONLY	8.2	29.4	44	1430	18.9	26.93
F-2	97130-2	9.5L-15/8	TT TIRE ONLY	9.5	30.8	48	1870	30.2	40.48
F-2	97135-2	11L-15/8	TT TIRE ONLY	11	32	44	2090	34.6	45.8
F-2	97137-2	4.00-16/4	TT TIRE ONLY	4.3	25.2	49	660	15.1	12.96
F-2	97140-2	5.50-16/4	TT TIRE ONLY	5.9	28.1	40	860	13.9	15.82
F-2	97145-2	6.00-16/6	TT TIRE ONLY	6.3	29.1	52	1140	18.9	20.79
F-2	97150-2	6.50-16/6	TT TIRE ONLY	6.8	30	48	1230	18.3	24.79
F-2	97155-2	7.50-16/8	TT TIRE ONLY	8	31.8	56	1710	24.6	37.18
F-2	97160-2	10.00-16/8	TT TIRE ONLY	10.8	35.2	44	2340	32.8	53.26
F-2	97165-2	11.00-16/8	TT TIRE ONLY	12.4	38.1	40	2600	30.2	70.58
F-2	97170-2	7.50-18/6	TT TIRE ONLY	8	33.8	44	1610	26.5	34.54
F-2	97175-2	4.00-19/4	TT TIRE ONLY	4.4	28.2	52	715	15.1	15.05
F-2	97152-2	6.50-20/8	TT TIRE ONLY	7.1	33.9	61	1905	22.7	35.29
F-2	97158-2	7.50-20/8	TT TIRE ONLY	8	35.8	54	2250	26.5	42.24

[View Samson F-2A Series Tires](#)



Features & Benefits

- Wide foot print and more surface contact allows for even better steering control and resistance to side slip.
- Designed to resist stubble punctures.
- Self cleaning tread design enhanced steering performance.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
F-2A	97700-2	10.00-16/10	TT TIRE ONLY	10.8	35.2	52	2600	26.5	50.2
F-2A	97705-2	10.00-16/10	TBLS	10.8	35.2	52	2600	26.5	53.33
F-2A	97708-2	11.00-16-10	TT TIRE ONLY	12.4	38.1	52	3080	29	64.88
F-2A	97710-2	11.00-16-12	TT TIRE ONLY	12.4	38.1	60	3420	29	66.04
F-2A	97715-2	11.00-16-10	TBLS	12.4	38.1	52	3080	29	68.38
F-2A	97718-2	11.00-16-12	TBLS	12.4	38.1	60	3420	29	68.4
F-2A	97720-2	14L-16.1-10	TBLS	14	38.8	43	3420	22.7	93
F-2A	97722-2	14L-16.1-12	TBLS	14	38.8	52	3860	22.7	86
F-2A	97725-2	16.5L-16.1/8FI	TBLS	16.5	42.2	32	3520	37.8	109

[View Samson I-1 Series Tires](#)



Features & Benefits

- Outstanding flotation use
- Easy steering from the heavy grooved ribs
- Extra wide design
- DOT Approved

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-1	97180-2	8.5L-14/6	TT TIRE ONLY	8.5	28.4	36	1870	7.6	20.55
I-1	97185-2	9.5L-14/8	TT TIRE ONLY	9.5	29.2	44	2400	8.2	24.44
I-1	97190-2	11L-14/6	TT TIRE ONLY	11	29.6	28	2040	8.2	30.1
I-1	97195-2	5.90-15/4	TT TIRE ONLY	6.1	26.2	36	1140	7.6	13.4
I-1	97265-2	5.70-15/6	TT TIRE ONLY	5.9	25.7	48	1490	8.2	12.87
I-1	97200-2	6.70-15/6	TT TIRE ONLY	6.7	27.7	44	1610	7.6	14.94
I-1	97205-2	7.60-15/8	TT TIRE ONLY	7.6	28.9	52	2090	7.6	21.67
I-1	97206-2	7.60-15/8	TBLS	7.6	28.9	52	2090	7.6	23.06
I-1	97210-2	9.5L-15/8	TT TIRE ONLY	9.5	30.2	44	2470	8.2	25.39
I-1	97212-2	9.5L-15/8	TBLS	9.5	30.2	44	2470	8.2	26.77
I-1	97232-2	9.5L-15/12	TBLS	9.5	30.2	64	3150	8.2	31
I-1	97215-2	10.00-15/8	TBLS	10.8	33.6	40	3200	10.7	40.92
I-1	97220-2	11L-15/8	TT TIRE ONLY	11	30.6	36	2540	8.2	30.65
I-1	97225-2	11L-15/8	TBLS	11	30.6	36	2540	8.2	32.56
I-1	97231-2	11L-15/12	TBLS	11	30.6	52	3200	8.2	34
I-1	97230-2	12.5L-15/10	TT TIRE ONLY	12.5	32.4	44	3410	8.8	35.71
I-1	97233-2	12.5L-15-10	TBLS	12.5	32.4	44	3420	8.8	41
I-1	97234-2	12.5L-15-12	TBLS	12.5	32.4	52	3860	8.8	42
I-1	97235-2	27X9.50-15/8	TBLS	9	27	60	1870	12	26.99
I-1	97240-2	6.00-16/6	TT TIRE ONLY	6.3	28	44	1815	8.2	15.62
I-1	97245-2	11L-16/8	TT TIRE ONLY	11	31.6	36	2680	8.2	32.96
I-1	97250-2	12.5L-16/10	TT TIRE ONLY	12.5	33.4	44	3520	8.8	38.7
I-1	97251-2	12.5L-16/12	TT TIRE ONLY	12.5	33.4	52	3960	8.8	38.7
I-1	97252-2	14L-16.1/8	TBLS	14	37	32	3860	12	59
I-1	97253-2	14L-16.1/12	TBLS	14	37	45	4680	12	61
I-1	97254-2	16.5L-16.1/10	Tubless	16.5	40.3	36	5192	15	84
I-1	97255-2	16.5L-16.1/14	Tubless	16.5	40.3	48	6380	15	89

[View Samson I-1E Series Tires](#)



Features & Benefits

- Outstanding flotation use. Non-highway service/low speed applications.
- Easy steering from the heavy grooved ribs.
- Economy

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-1E	97211-2	9.5L-15/8	TT TIRE ONLY	9.8	28.8	44	2470	7.6	23.19
I-1E	97214-2	9.5L-15/8	TBLS	9.8	28.8	44	2470	7.6	24.57
I-1E	97219-2	11L-15/8	TT TIRE ONLY	10.9	29.4	36	2540	7.6	25.06
I-1E	97228-2	11L-15/8	TBLS	10.9	29.4	36	2540	7.6	26.38

[View Samson FI Series Tires](#)

Features & Benefits

- D.O.T. approved for intermittent highway speeds
- 5 rib design improves stability

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
FI	97280-2	9.5L-15FI-10	TBLS	9.5	30.2	75	3080	12	43
FI	97284-2	11L-15FI-12	TBLS	11	30.6	90	3410	12	54
FI	97286-2	12.5L-15FI-12	TBLS	12.5	32.4	90	4680	12	68.6
FI	97288-2	14L-16.1/8FI	TL	14	37	45	4300	12	62
FI	97290-2	16.5L-16.1/8FI	TL	16.5	40.3	45	5520	15.1	81

[View Samson HF-1 Series Tires](#)

Features & Benefits

- High flotation ribbed turf tire.
- Used in golf course work, hay baling, and turf work.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
HF-1	97260-2	31X13.50-15/10	TBLS	13.8	30.8	55	2790	12.6	50.73

[View Samson HF-1A Series Tires](#)



Features & Benefits

- High flotation ribbed turf tire.
- Used in golf course work, hay baling, and turf work.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
HF-1A	97270-2	10.5/65-16/14	TT TIRE ONLY	10.8	29.7	77	*2910/**4180	10.1	28.38
HF-1A	97274-2	13.0/65-18/16	TT TIRE ONLY	13.2	35	71	*4300/**6170	12.6	74.4

[View Samson I-1A Series Tires](#)



Features & Benefits

- Modern universal tread pattern for a wide range of agricultural uses.
- Low-section implement tires with high load capacity with minimum soil compaction

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-1A	93000-2	7.00-12/6	TL	7.9	26.3	36	1520	10.1	18

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-1A	93002-2	10.0/80-12/10	TL	10.4	28	57	3200	11.3	30
I-1A	93004-2	10.0/75-15.3/12	TL	10.4	29.9	68	3750	10.7	35
I-1A	93006-2	11.5/80-15.3/12	TL	11.4	33.3	59	4800	13.2	46
I-1A	93008-2	12.5/80-15.3/14	TL	12.1	35	62	5840	12.6	54
I-1A	93010-2	6.00-16/6	TL	6.7	28	40	1520	8.8	18
I-1A	93012-2	10.5/65-16/14	TL	10.8	29.7	77	4190	13.9	37
I-1A	93014-2	10.5/80-18/12	TL	10.8	34.8	62	4800	13.2	45
I-1A	93016-2	12.5/80-18/14	TL	12.1	38	62	6390	12.6	64
I-1A	93018-2	13.0/65-18/16	TL	13.2	35	71	6170	15.1	56
I-1A	93020-2	15.0/70-18/16	TL	15.4	39	62	7600	13.9	82

[View Samson I-1B Series Tires](#)

Features & Benefits

- Unique tread pattern with rolling rib profile without any lateral tread elements make it ideal for meadowland use or soil Cultivation.
- Low-section implement tires with high load capacity with minimum soil compaction

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-1B	93030-2	400/60-15.5/10	TL	15.9	34.4	41	5350	15.7	65
I-1B	93032-2	400/60-15.5/14	TL	15.9	34.4	52	6390	15.7	67

[View Samson I-1C Series Tires](#)




**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720

Features & Benefits

- Modern universal tread pattern for a wide range of agricultural uses
- Low-section implement tires with high load capacity with minimum soil compaction
- Designed for on and off road implement applications

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-1C	93040-2	15.0/55-17/10	TL	15.4	33.5	38	4670	13.9	57
I-1C	93042-2	15.0/55-17/14	TL	15.4	33.5	54	5670	13.9	59

SKU: category-samson-farm