

SAMSON SKID STEER / BACKHOE CATEGORY



SAMSON

[View Samson R-4E Series Tires](#)



Features & Benefits

- Wide tread design to decrease soil compaction.
- Puncture resistant tread design.
- Deep tread pattern to provide additional traction.
- Wear resistant compound to prolong tire service life.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4E	96226-2	340/80R18 TL R-4E(143A8)	TL	13.5	39.4	58	6010	35.3	114.4
R-4E	96228-2	280/80R20	TL	11.1	37.6	58	4540	32.7	85
R-4E	96230-2	340/80R20	TL	13.5	41.4	58	6150	35.2	117
R-4E	96232-2	400/70R20	TL	15.9	42	58	7150	30.7	135

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4E	96200-2	17.5LR24	TBLS	17.5	49.2	46	7820	45.4	197
R-4E	96202-2	17.5L(460/70)R24 STEEL BELT	TL	17.9	49.4	58	9650	45.4	207.9
R-4E	96206-2	19.5LR24	TBLS	19.5	52	44	8820	47.9	248
R-4E	96205-2	19.5LR24	TBLS	19.5	52	44	8820	47.9	240
R-4E	96208-2	540/70424	TBLS	21.7	53.8	35	8050	49.8	288
R-4E	96210-2	540/70(21L)R24 STEEL BELT	TL	21.7	53.8	46	10200	49.8	297.3
R-4E	96212-2	400(15.5)/80R24 STEEL BELT	TL	15.9	49.2	58	8800	44.1	190
R-4E	96215-2	400(15.5)/80R24 STEEL BELT	TL	15.9	49.2	73	10500	44.1	197.1
R-4E	96217-2	400(405)/70R24 STEEL BELT	TL	15.9	46.1	58	7850	38.4	168.7
R-4E	96218-2	400(405)/70R24 STEEL BELT	TL	15.9	46.1	73	9350	38.4	175.9
R-4E	96216-2	400/70R24 STEEL BELT	TL	15.9	46.1	46	6400	38.4	177.6
R-4E	96220-2	440/80(16.9)R24 STEEL BELT	TL	17.4	51.7	58	10200	46.6	224.9
R-4E	96222-2	480/80(18.4)R26 STEEL BELT	TL	18.9	56.2	46	9900	47.9	280.6
R-4E	96224-2	440/80(16.9)R28 STEEL BELT	TL	17.4	55.7	46	8800	47.9	251.3

[View Samson R-4B Series Tires](#)

Features & Benefits

- Provides tight center bars for excellent road-ability.
- Reinforced sidewall with curb and rim guard to provide extra protection against rim and sidewall damage.
- Deep tread lugs deliver excellent traction in muddy soil conditions.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4B	99110-2	16.9-24/12	TBLS	16.9	51.5	38	7165	35.3	191.68
R-4B	99120-2	17.5L-24/12	TBLS	17.5	48.9	38	6605	32	163.25
R-4B	99130-2	19.5L-24/12	TBLS	19.5	51.7	33	7605	35.9	187.87
R-4B	99140-2	21L-24/12	TBLS	21	54.3	32	8545	36.5	233.47

[View Samson R-4A Series Tires](#)



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720



Features & Benefits

- Premium - Ultimate backhoe tire.
- Extra wide tread design for high flotation and super stability in extreme conditions.
- Large center bars for superior road-ability, extra deep tread for superior traction.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4A	99030H-2	19.5L-24/14	TBLS	19.5	51.7	38	8145	35.9	214.92
R-4A	99040H-2	21L-24/16	TBLS	21	54.3	41	9920	40.1	242.47

[View Samson R-4 Series Tires](#)



Features & Benefits

- Wide foot print for high flotation and stability, delivers excellent traction.
- Premium tread width and depth provides increased tire life and trouble-free performance.
- Economy

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4	99160-2	14.9-24/12	TBLS	14.9	48.9	42	6395	32	153.45
R-4	98010L-2	16.9-24/12	TBLS	16.9	51.5	35	5465	32.8	162.52
R-4	98020L-2	17.5L-24/12	TBLS	17.5	48.9	33	4255	33.4	154.25
R-4	98030L-2	19.5L-24/12	TL	19.5	51.7	33	7605	37.2	
R-4	98040L-2	21L-24/12	TBLS	21	54.3	28/*28	5310/*5840	37.2	233.47



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720

[View Samson R-4D Series Tires](#)



Features & Benefits

- Durable tread pattern for high flotation and super stability.
- Designed against resistance to chunking and tearing.
- Deep tread lugs deliver excellent traction in muddy soil conditions.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4D	98075-2	18.4-26/12	TBLS	18.4	56.1	33/*32	6580/*5840	36.5	225.32
R-4D	98070-2	16.9-28-12	TBLS	16.9	55.5	35	5840	35.3	183.3
R-4D	98072-2	16.9-28-14	TBLS	16.9	55.5	41	6615	35.3	196.53

[View Samson R-4 IND Series Tires](#)



Features & Benefits

- Bar angle provides superior traction off road and good wear during road transportation.
- Heavy duty design for excellent ride, snag resistance and long wear.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4 IND	99215-2	340(12.5)/80-18-12	TL	13.5	39.4	58	6005	34.6	101
R-4 IND	99220-2	340(12.5)/80-20-12	TL	13.5	41.4	58	6175	34.6	111
R-4 IND	99210-2	400/70-20-14	TL	15.9	42	58	7165	40.3	138
R-4 IND	99205-2	480/80-26 -14	TL	18.9	56.2	35	7850	42.8	236
R-4 IND	99200-2	440/80-28-14	TL	17.4	55.7	35	6950	42.8	229



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720

[View Samson F-3 Series Tires](#)



Features & Benefits

- Applicable for agricultural tractors in industrial service and backhoes.
- Deep tread offers excellent impact, cut and puncture resistance.
- Provides superior traction on hard soil, asphalt and concrete.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
F-3	19501-2	11L-15/10	TBLS 11		32	52	2340	16	55.92
F-3	19502-2	11L-15/14	TBLS 11		32	73	2855	16	61.13
F-3	19520-2	11L-16/10	TBLS 11		33	52	2470	16	59.55
F-3	19521-2	11L-16/14	TBLS 11		33	73	3055	16	62.44

[View Samson GLR05 Series Tires](#)



Features & Benefits

- All Steel radial casing
- Extremely strong sidewall strength
- Increased tread wear on abrasive surfaces

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
GLR05	42500-2	10R16.5	TBLS 10.4		30.3	55	3970	30.2	76
GLR05	42505-2	12R16.5	TBLS 12		32.7	55	5680	34	100

[View Samson GLR25 Series Tires](#)



Features & Benefits

- Reinforces radial construction provides better traction and smoother ride than bias tires.
- All-steel construction provides superior puncture resistance and longer life.
- Incredible traction in slippery, muddy terrain.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
GLR25	42510-2	10R16.5 (265/70R16.5)	TL		30.1	55	3970	24.6	74
GLR25	42515-2	12R16.5 (305/70R16.5)	TL		32.7	55	5680	29	96

[View Samson L-2B Series Tires](#)



Features & Benefits

- Ultra heavy duty skid-steer tire.
- Triple step lug provides self cleaning capabilities.
- Extra deep tread for superior traction and longer tread life.
- Rim guard

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
L-2B	16000-2	5.70x12/8	TBLS	5.7	22.4	90	1875	18.9	17.38
L-2B	16002-2	23X8.50-12/8	TBLS	8.4	22.6	65	2170	18.9	24.64
L-2B	16004-2	27X8.50-15/10	TBLS	8.4	25.9	70	2270	18.9	31.9



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720

[View Samson LD180 Series Tires](#)



Features & Benefits

- Robust, reinforced tread lug provides superior traction.
- Advanced compound resists tears and punctures.
- Reinforced sidewall for extra durability.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
LD180	16070-2	18x8.50-10NHS	TL	7.5	18.5	22	825	16.4	13.2

[View Samson L-2E Series Tires](#)



Features & Benefits

- Ultra heavy duty skid-steer tire.
- Features reinforced sidewalls and rim guard that provides extra protection against sidewall damage.
- Extra deep tread for superior traction and longer tread life.
- Rim guard

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
L-2E	16050-2	10-16.5/8	TBLS	10.4	31.4	59	4140	21.4	54.55
L-2E	16054-2	10-16.5/10	TBLS	10.4	31.4	75	4710	21.4	55.28
L-2E	16028-2	10-16.5/12	TBLS	10.4	31.4	90	5240	21.4	61.36
L-2E	16030-2	10-16.5/14	TBLS	10.4	31.4	104	6040	21.4	62.52
L-2E	16038-2	12-16.5/14	TBLS	12.36	33.3	90	6780	26.5	82.62
L-2E	16040-2	12-16.5/16	TBLS	12.36	33.3	110	7920	26.5	87.01

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
L-2E	16042-2	33X15.50-16.5/12	TBLS	15.5	33	61	8005	32.1	95.9

[View Samson L-2D Series Tires](#)

Features & Benefits

- Durable tread pattern for high flotation and super stability.
- Designed against resistance to chunking and tearing.
- Features also included rim guard and heavy duty sidewall.
- Economy

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
L-2D	16051-2	10-16.5/8	TBLS	10.4	30.4	59	4140	20.2	41.95
L-2D	16052-2	10-16.5/10	TBLS	10.4	30.4	75	4710	20.2	43.16
L-2D	16055-2	12-16.5/10	TBLS	11.18	33.1	65	5600	23.9	52.16
L-2D	16056-2	12-16.5/12	TBLS	11.18	33.1	80	6320	23.9	53.57
L-2D	16058-2	14-17.5/16	TBLS	13.7	36.3	100	8260	27.7	101.91
L-2D	16059-2	15-19.5/16	TBLS	15.3	40.1	80	10880	31.5	127.97
L-2D	19532-2	10.5/80-18/12	TBLS	10.8	34.7	62	3230	20.2	59.44

[View Samson L-4A Series Tires](#)

Features & Benefits

- Severe service skid-steer tire with non-directional design for packed soil, or hard surface applications.

- Reinforced sidewall with curb and rib guard that provides extra protection against rim and sidewall damage.
- Reinforced for superior tread stability and greater penetration resistance.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
L-4A	16150-2	10-16.5/10	TBLS	10.4	30.4	75	4710	34	71.63
L-4A	16152-2	10-16.5/12	TBLS	10.4	30.4	90	5240	34	71.59
L-4A	16160-2	12-16.5/12	TBLS	12.1	32.7	80	6320	42.2	97.55
L-4A	16162-2	12-16.5/14	TBLS	12.1	32.7	90	6780	42.2	99.93
L-4A	16170-2	14-17.5/16	TBLS	13.7	36.3	100	8260	47.2	148.63
L-4A	16180-2	15-19.5/14	TBLS	15.3	40.1	70	10060	47.2	170.04
L-4A	16182-2	12-16.5/14	TBLS	12.1	32.7	90	6780	42.2	112.13
L-4A	16151-2	10-16.5/10	TBLS	10.4	30.4	75	4710	34	68.13
L-4A	16153-2	10-16.5/12	TBLS	10.4	30.4	90	5240	34	68.45
L-4A	16164-2	12-16.5/12	TBLS	12.1	32.7	80	6320	42.2	94.28
L-4A	16163-2	12-16.5/14	TBLS	12.1	32.7	90	6780	42.2	95.64
L-4A	16171-2	14-17.5/16	TBLS	13.7	36.3	100	8260	47.2	148.63
L-4A	16174-2	15-19.5/14	TBLS	15.3	40.1	70	10060	47.2	165.26

[View Samson L-5 Series Tires](#)



Features & Benefits

- Extra deep tread provides excellent rock type damage resistance and long tread life.
- Open non-directional tread pattern provides all around traction with excellent self cleaning.
- Solid center line section provides long wear, smooth ride and is ideal for high torque applications and hard rock quarry service.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
L-5	16190-2	32X11-16.5/10	TBLS	12.1	32.7	60	5340	48.5	106
L-5	16195-2	34X12.5-16.5/12	TBLS	12.1	34.3	65	5600	52	119.7

[View Samson R-4C Series Tires](#)



Features & Benefits

- Durable tread pattern for high flotation and super stability.
- Designed against resistance to chunking and tearing.
- Features also include rim guard and heavy duty sidewall.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
R-4C	19530-2	10.5/80-18/14	TBLS	10.8	34.7	70	3375	32	77.84
R-4C	19534-2	12.5/80-18/16	TBLS	12.1	37.9	71	4805	32	115.43
R-4C	19536-2	10-16.5/12	TBLS	10.4	30.4	90	5240	21.4	61.38
R-4C	19537-2	12-16.5/14	TBLS	12.1	32.7	90	6780	26.5	86.33

[View Samson I-3D Series Tires](#)



Features & Benefits

- Moderate traction tread, drive wheel.
- Backhoe use.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-3D	59010-2	31x15.50-15/12	TBLS	15.4	31.2	75	3705	26.5	74.8
I-3D	59020-2	26x12-12/10	TBLS	12.1	25.5	65	3595	22.7	37.71

[View Samson I-3C Series Tires](#)



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720



Features & Benefits

- Light traction tread, drive wheel.
- Backhoe use.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-3C	47025-2	550/60-22.5/16	TBLS	21.1	49.4	44	*11670/**8260	31.5	207
I-3C	47028-2	600/55-22.5/16	TBLS	23.6	48.2	37.7	7590	32.8	227.37
I-3C	47020-2	400/60-15.5/14	TL	15.9	34.4	52	*7165/**4410	25.2	76
I-3C	47022-2	500/60-22.5/16	TL	19.8	46.2	71	*13200/**9350	32.8	227
I-3C	47026-2	600/50-22.5/16	TL	24.1	46.1	46	*12300/**8810	32.8	254
I-3C	47030-2	700/50-22.5/12	TBLS	27.6	50	32	*12330/**8810	34	345.82
I-3C	47032-2	700/50-26.5/16	TL	28	52.5	35	*12800/**9100	32.8	334
I-3C	59025-2	16.5L-16.1/10	TBLS	16.5	41.2	40	5680	29	116

[View Samson I-3 Series Tires](#)



Features & Benefits

- Deep tread for excellent traction and self-cleaning.
- Strong nylon carcass for stability and durability.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-3	93050-2	10.5/80-18/12	TL	10.8	35.7	62	*4850/**3420	25.2	58
I-3	93054-2	12.5/80-18/12	TL	12.1	38.9	54	*5840/**4080	25.2	88

[View Samson I-3A Series Tires](#)



Features & Benefits

- Deep tread for excellent traction and self-cleaning.
- Strong nylon carcass for stability and durability.

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-3A	93058-2	15.5/80-24/12	TL	15.6	49.7	44	*9090/**6390	44.1	172

[View Samson I-3F Series Tires](#)



Features & Benefits

- Unique traction designed for many agricultural applications
- Engineered for on and off road services in any weather

Individual Data Sheet	SKU	Size	Type	Section Width	Overall Diameter	Inflation Pressure	Max Load	Tread Depth	Tire Weight
I-3F	93066-2	10.0/75-15.3/12	TL	10.4	30.7	68	3750	27.1	43
I-3F	93068-2	11.5/80-15.3/10	TL	11.4	34.1	49	3000	18.9	55
I-3F	93070-2	11.5/80-15.3/14	TL	11.4	34.1	69	3750	18.9	57

SKU: category-samson-farm-skid-steer-backhoe



**NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.**
1441 South Main St.
North Canton, Ohio 44720