



Date: 3/19/14

1441 South Main St. | North Canton, Ohio 44720
Phone: 330.368.4200 | Fax: 330.368.4224

MB2014003-S

MARKETING BULLETIN

Samson Premium Long Haul Decoupling Groove Tire!



We are pleased to announce orders are now being accepted for our Samson GL116S decoupling groove tires.

Premium 19/32nds long haul highway steer tire with decoupler groove to help resist irregular wear for an even footprint.

Technologically advanced tread compound for low rolling resistance and improved fuel economy.

Enhanced bead and belt package for increased tire performance and multiple retreads.



Additional siping helps inhibit onset of irregular wear and improve wet traction.

Cat #	Size	Type	Design	GTC Pattern	FET	Speed Symbol	Load Index	Section Width (in.)
86300-2	11R22.5/14	TL	Samson Radial Truck GL116S	GL116S	25.33	M	S144/D142	11.0
86305-2	11R22.5/16	TL	Samson Radial Truck GL116S	GL116S	29.30	M	S146/D143	11.0
86310-2	11R24.5/14	TL	Samson Radial Truck GL116S	GL116S	29.30	M	S146/D143	11.0
86315-2	11R24.5/16	TL	Samson Radial Truck GL116S	GL116S	34.49	L	S149/D146	11.0
86320-2	285/75R24.5/14	TL	Samson Radial Truck GL116S	GL116S	25.33	M	S144/D141	11.1
86325-2	285/75R24.5/16	TL	Samson Radial Truck GL116S	GL116S	31.19	L	S147/D144	11.1
86330-2	295/75R22.5/14	TL	Samson Radial Truck GL116S	GL116S	25.33	M	S144/D141	11.7
86335-2	295/75R22.5/16	TL	Samson Radial Truck GL116S	GL116S	29.30	L	S146/D143	11.7

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
86300-2	11R22.5/14	41.5	80.0	105	S6175/D5840	8.25	18.9	109.0
86305-2	11R22.5/16	41.5	80.0	120	S6610/D6005	8.25	18.9	109.0
86310-2	11R24.5/14	43.5	80.0	105	S6610/D6005	8.25	18.9	119.0
86315-2	11R24.5/16	43.5	75.0	120	S7160/D6610	8.25	18.9	119.0
86320-2	285/75R24.5/14	41.3	80.0	110	S6175/D5675	8.25	18.9	108.0
86325-2	285/75R24.5/16	41.3	75.0	120	S6780/D6175	8.25	18.9	108.0
86330-2	295/75R22.5/14	39.9	80.0	110	S6175/D5675	9.00	18.9	99.0
86335-2	295/75R22.5/16	39.9	75.0	120	S6610/D6005	9.00	18.9	99.0