



Date: 4/8/14

1441 South Main St. | North Canton, Ohio 44720  
Phone: 330.368.4200 | Fax: 330.368.4224

MB2014012-A

## MARKETING BULLETIN

### Advance GL281A



We are pleased to announce orders are now being accepted for our Advance GL281A tires.

Features include:

Optimized shoulder profile designing

Completely new crown designing

Optimized groove designing guarantees wet skid resistance



Cat #	Size	Type	Design	GTC Pattern	FET	Speed Symbol	Load Index	Section Width (in.)
281001A	11R22.5/14	TL	Advance Radial Truck GL281A	GL281A	25.33	M	S144/D142	11.0
281002A	11R22.5/16	TL	Advance Radial Truck GL281A	GL281A	29.30	M	S146/D143	11.0
281003A	11R24.5/14	TL	Advance Radial Truck GL281A	GL281A	29.30	M	S146/D143	11.0
281004A	11R24.5/16	TL	Advance Radial Truck GL281A	GL281A	34.49	L	S149/D146	11.0
281005A	285/75R24.5/14	TL	Advance Radial Truck GL281A	GL281A	25.33	M	S144/D141	11.1
281006A	285/75R24.5/16	TL	Advance Radial Truck GL281A	GL281A	31.19	L	S147/D144	11.1
281007A	295/75R22.5/14	TL	Advance Radial Truck GL281A	GL281A	25.33	M	S144/D141	11.7
281008A	295/75R22.5/16	TL	Advance Radial Truck GL281A	GL281A	29.30	L	S146/D143	11.7

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
281001A	11R22.5/14	41.5	80.0	105	S6175/D5840	8.25	18.9	106
281002A	11R22.5/16	41.5	80.0	120	S6610/D6005	8.25	18.9	106
281003A	11R24.5/14	43.5	80.0	105	S6610/D6005	8.25	18.9	115
281004A	11R24.5/16	43.5	75.0	120	S7160/D6610	8.25	18.9	115
281005A	285/75R24.5/14	41.3	80.0	110	S6175/D5675	8.25	18.9	110
281006A	285/75R24.5/16	41.3	75.0	120	S6780/D6175	8.25	18.9	110
281007A	295/75R22.5/14	39.9	80.0	110	S6175/D5675	9.00	18.9	101
281008A	295/75R22.5/16	39.9	75.0	120	S6610/D6005	9.00	18.9	101