



Date: 4/11/14

1441 South Main St. | North Canton, Ohio 44720
Phone: 330.368.4200 | Fax: 330.368.4224

MB2014013-S

MARKETING BULLETIN

Highway Service Mobile Crane Tire



GL904



GL905

We are pleased to announce orders are now being accepted for our new Samson GL904 and GL905 Highway Service Mobile Crane Tires.

Features include:

- High speed service
- Reduced noise design
- Long wear
- Even footprint
- Durable compound

Cat #	Size	Type	Design	GTC Pattern	FET	Speed Symbol	Load Index	Section Width (in.)
41430-2	385/95R24(1400R24)	TBLS	Samson Radial E-2 3 stars	GL904	0.00	F	170	15.2
41432-2	385/95R25(1400R25)	TBLS	Samson Radial E-2 3 stars	GL904	0.00	F	170	15.2
41440-2	445/95R25(16.00R25)	TBLS	Samson Radial E-2 2 stars	GL905	0.00	F	174	17.2
41442-2	520/85R25 (20.5R25)	TBLS	Samson Radial E-2 2 stars	GL905	0.00	E	179	20.7

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
41430-2	385/95R24(1400R24)	53.7	50.0	130	13230	10.00/1.5	25.8	303.49
41432-2	385/95R25(1400R25)	53.7	50.0	130	13230	10.00/1.5	25.8	303.49
41440-2	445/95R25(16.00R25)	58.3	50.0	130	14800	11.25/2.0	31.5	255.70
41442-2	520/85R25 (20.5R25)	58.1	43.0	100	17100	17.00	37.8	518.00