



1441 South Main St. | North Canton, Ohio 44720  
 Phone: 330.368.4200 | Fax: 330.368.4224

**MARKETING BULLETIN**  
 Date: 09-29-2014 • MB2014031-A

## Advance Rear Farm Changes


The following 3 Advance rear farm Agri-Trac R-1 tires will no longer be produced in the R-1 pattern but will now be produced in the R-1S pattern. Attached is a picture of the R-1S.



**Features and Benefits of the R-1S Include:**

- Bar angle provides superior traction in the field and good wear during road transportation.
- Heavy duty design for excellent ride, snag resistance and long wear.
- Variety of sizes for use with tractors, and combines.

OLD Cat#	<u>NEW Cat #</u>	Size	OLD GTC Pattern	<u>NEW GTC Pattern</u>
97002G	96002G	8.3-24/8	R-1	R-1S
97003G	96003G	9.5-20/8	R-1	R-1S
97004G	96004G	9.5-24/8	R-1	R-1S



Cat #	Size	Type	Design	GTC Pattern	Ply Rating	Speed Symbol	Load Index	Section Width (in.)
96002G	8.3-24/8	TT	Farm Rear R-1S	R-1S	8	A6	N/A	8.3
96003G	9.5-20/8	TT	Farm Rear R-1S	R-1S	8	A6	N/A	9.5
96004G	9.5-24/8	TT	Farm Rear R-1S	R-1S	8	A6	N/A	9.4

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
96002G	8.3-24/8	39.1	20	46	2115	7	37.8	49
96003G	9.5-20/8	37.4	20	41	2105	8	41.6	48
96004G	9.5-24/8	41.3	20	41	2445	8	41.6	59