



1441 South Main St. | North Canton, Ohio 44720  
 Phone: 330.368.4200 | Fax: 330.368.4224

**MARKETING BULLETIN**  
 Date: 09-24-2014 • MB2014038-A

**The Advance GL115S is Now SmartWay Approved!**



We are pleased to announce that the Advance GL115S tires are SmartWay approved.

**Features and Benefits Include:**

- Premium 19/32nds long haul highway steer tire with decoupler groove to help resist irregular wear for an even footprint.
- Technologically advanced tread compound for low rolling resistance and improved fuel economy.
- Enhanced bead and belt package for increased tire performance and multiple retreads.



Cat #	Size	Type	Design	GTC Pattern	FET	Speed Symbol	Load Index	Section Width (in.)
115001A	11R22.5/14	TL	Advance Radial Truck GL115S	GL115S	25.33	M	S144/D142	11.0
115002A	11R22.5/16	TL	Advance Radial Truck GL115S	GL115S	29.30	M	S146/D143	11.0
115003A	11R24.5/14	TL	Advance Radial Truck GL115S	GL115S	29.30	M	S146/D143	11.0
115004A	11R24.5/16	TL	Advance Radial Truck GL115S	GL115S	34.49	L	S149/D146	11.0
115005A	285/75R24.5/14	TL	Advance Radial Truck GL115S	GL115S	25.33	M	S144/D141	11.1
115006A	285/75R24.5/16	TL	Advance Radial Truck GL115S	GL115S	31.19	L	S147/D144	11.1
115007A	295/75R22.5/14	TL	Advance Radial Truck GL115S	GL115S	25.33	M	S144/D141	11.7
115008A	295/75R22.5/16	TL	Advance Radial Truck GL115S	GL115S	29.30	L	S146/D143	11.7

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
115001A	11R22.5/14	41.5	80.0	105	S6175/D5840	8.25	18.9	109.0
115002A	11R22.5/16	41.5	80.0	120	S6610/D6005	8.25	18.9	109.0
115003A	11R24.5/14	43.5	80.0	105	S6610/D6005	8.25	18.9	119.0
115004A	11R24.5/16	43.5	75.0	120	S7160/D6610	8.25	18.9	119.0
115005A	285/75R24.5/14	41.3	80.0	110	S6175/D5675	8.25	18.9	108.0
115006A	285/75R24.5/16	41.3	75.0	120	S6780/D6175	8.25	18.9	108.0
115007A	295/75R22.5/14	39.9	80.0	110	S6175/D5675	9.00	18.9	99.0
115008A	295/75R22.5/16	39.9	75.0	120	S6610/D6005	9.00	18.9	99.0