



1441 South Main St. | North Canton, Ohio 44720
 Phone: 330.368.4200 | Fax: 330.368.4224

MARKETING BULLETIN
 Date: 09-24-2014 • MB2014039-S

The Samson GL160D is Now SmartWay Approved!



We are pleased to announce that the Samson GL160D tires are SmartWay approved.

Features and Benefits Include:

- Premium 26/32nds long haul highway close shoulder drive tire for extended mileage and even tread wear.
- Advanced tread compound for low rolling resistance and increased fuel economy.
- Tapered groove technology and stone ejectors to minimize stone retention and increasing casing life.



Cat #	Size	Type	Design	GTC Pattern	Ply Rating	Speed Symbol	Load Index	Section Width (in.)
160001-2	11R22.5	TL	Samson GL160D	GL160D	14	M	S144/D142	11
160002-2	11R22.5	TL	Samson GL160D	GL160D	16	M	S146/D143	11
160003-2	11R24.5	TL	Samson GL160D	GL160D	14	M	S146/D143	11
160004-2	11R24.5	TL	Samson GL160D	GL160D	16	L	S149/D146	11
160005-2	285/75R24.5	TL	Samson GL160D	GL160D	14	M	S144/D141	11.1
160006-2	285/75R24.5	TL	Samson GL160D	GL160D	16	L	S147/D144	11.1
160007-2	295/75R22.5	TL	Samson GL160D	GL160D	14	M	S144/D141	11.7
160008-2	295/75R22.5	TL	Samson GL160D	GL160D	16	L	S146/D143	11.7

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
160001-2	11R22.5	41.5	80	105	S6175/D5840	8.25	25.8	112
160002-2	11R22.5	41.5	80	120	S6610/D6005	8.25	25.8	112
160003-2	11R24.5	43.5	80	105	S6610/D6005	8.25	25.8	121
160004-2	11R24.5	43.5	75	120	S7160/D6610	8.25	25.8	121
160005-2	285/75R24.5	41.3	80	110	S6175/D5675	8.25	25.8	117
160006-2	285/75R24.5	41.3	75	120	S6780/D6175	8.25	25.8	117
160007-2	295/75R22.5	39.9	80	110	S6175/D5675	9	25.8	108
160008-2	295/75R22.5	39.9	75	120	S6610/D6005	9	25.8	108