



Mix and match your tire order per shipping container! Authorized distributors can mix and match any type of our Samson or Advance branded tires in one container shipment, including: MTR/Mobile Crane, Bias Truck, OTR/Logging, Industrial, Farm/Skid Steer and Solid/Giant Solid.

1441 South Main St. | North Canton, Ohio 44720
 Phone: 330.368.4200 | Fax: 330.368.4224

MARKETING BULLETIN
 Date: 10-21-2014 • MB2014044-A

The Advance GL281A is Now SmartWay Approved!



We are pleased to announce that the EPA has verified the Advance GL281A as SmartWay approved for Steer and Drive applications.

Features and Benefits:

- Premium 19/32nds all position tire with an enhanced bead and belt package for even footprint for increased tire mileage.
- Technologically advanced tread compound for low rolling resistance and improved fuel economy.
- Enhanced bead and belt package increases tire performance and multiple retreads.



Cat #	Size	Type	Design	GTC Pattern	Ply Rating	Speed Symbol	Load Index	Section Width (in.)
281001A	11R22.5	TL	Advance Radial Truck GL281A	GL281A	14	M	S144/D142	11.0
281002A	11R22.5	TL	Advance Radial Truck GL281A	GL281A	16	M	S146/D143	11.0
281003A	11R24.5	TL	Advance Radial Truck GL281A	GL281A	14	M	S146/D143	11.0
281004A	11R24.5	TL	Advance Radial Truck GL281A	GL281A	16	L	S149/D146	11.0
281005A	285/75R24.5	TL	Advance Radial Truck GL281A	GL281A	14	M	S144/D141	11.1
281006A	285/75R24.5	TL	Advance Radial Truck GL281A	GL281A	16	L	S147/D144	11.1
281007A	295/75R22.5	TL	Advance Radial Truck GL281A	GL281A	14	M	S144/D141	11.7
281008A	295/75R22.5	TL	Advance Radial Truck GL281A	GL281A	16	L	S146/D143	11.7

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
281001A	11R22.5	41.5	80.0	105	S6175/D5840	8.25	18.9	106
281002A	11R22.5	41.5	80.0	120	S6610/D6005	8.25	18.9	106
281003A	11R24.5	43.5	80.0	105	S6610/D6005	8.25	18.9	115
281004A	11R24.5	43.5	75.0	120	S7160/D6610	8.25	18.9	115
281005A	285/75R24.5	41.3	80.0	110	S6175/D5675	8.25	18.9	110
281006A	285/75R24.5	41.3	75.0	120	S6780/D6175	8.25	18.9	110
281007A	295/75R22.5	39.9	80.0	110	S6175/D5675	9.00	18.9	101
281008A	295/75R22.5	39.9	75.0	120	S6610/D6005	9.00	18.9	101