



1441 South Main St. | North Canton, Ohio 44720  
 Phone: 330.368.4200 | Fax: 330.368.4224

**MARKETING BULLETIN**  
 Date: 10-30-2014 • MB2014046-S

**The Samson GL116S is Now SmartWay Approved!**



We are pleased to announce that the Samson GL116S tires are SmartWay approved.

**Features and Benefits Include:**

- Premium 19/32nds long haul highway steer tire with decoupler groove to help resist irregular wear for an even footprint.
- Technologically advanced tread compound for low rolling resistance and improved fuel economy.
- Enhanced bead and belt package for increased tire performance and multiple retreads.



Cat #	Size	Type	Design	GTC Pattern	Ply Rating	Speed Symbol	Load Index	Section Width (in.)
86300-2	11R22.5	TL	Samson Radial Truck GL116S	GL116S	14	M	S144/D142	11.0
86305-2	11R22.5	TL	Samson Radial Truck GL116S	GL116S	16	M	S146/D143	11.0
86310-2	11R24.5	TL	Samson Radial Truck GL116S	GL116S	14	M	S146/D143	11.0
86315-2	11R24.5	TL	Samson Radial Truck GL116S	GL116S	16	L	S149/D146	11.0
86320-2	285/75R24.5	TL	Samson Radial Truck GL116S	GL116S	14	M	S144/D141	11.1
86325-2	285/75R24.5	TL	Samson Radial Truck GL116S	GL116S	16	L	S147/D144	11.1
86330-2	295/75R22.5	TL	Samson Radial Truck GL116S	GL116S	14	M	S144/D141	11.7
86335-2	295/75R22.5	TL	Samson Radial Truck GL116S	GL116S	16	L	S146/D143	11.7

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
86300-2	11R22.5	41.5	80.0	105	S6175/D5840	8.25	18.9	111
86305-2	11R22.5	41.5	80.0	120	S6610/D6005	8.25	18.9	111
86310-2	11R24.5	43.5	80.0	105	S6610/D6005	8.25	18.9	119
86315-2	11R24.5	43.5	75.0	120	S7160/D6610	8.25	18.9	119
86320-2	285/75R24.5	41.3	80.0	110	S6175/D5675	8.25	18.9	110
86325-2	285/75R24.5	41.3	75.0	120	S6780/D6175	8.25	18.9	110
86330-2	295/75R22.5	39.9	80.0	110	S6175/D5675	9.00	18.9	105
86335-2	295/75R22.5	39.9	75.0	120	S6610/D6005	9.00	18.9	105