



Mix and match your tire order per shipping container! Authorized distributors can mix and match any type of our Samson or Advance branded tires in one container shipment, including: MTR/Mobile Crane, Bias Truck, OTR/Logging, Industrial, Farm/Skid Steer and Solid/Giant Solid.

1441 South Main St. | North Canton, Ohio 44720  
 Phone: 330.368.4200 | Fax: 330.368.4224

**MARKETING BULLETIN**  
 Date: 12-15-2014 • MB2014053-A

**Please see below for our Advance R-1W 480/80R42 radial farm load and inflation chart:**

**480/80R42 148A8 TL ADVANCE**

30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Pressure	Unloaded Overall Width	Unloaded Overall Diameter	Loaded Radius	Rolling Circumference
2470lbs 1120kg	3080lbs 1400kg	3295lbs 1500kg	4130lbs 1875kg	2710lbs 1230kg	6psi 0.4bar	18.4in 467mm	72.8in 1850mm	34.3in 870mm	220in 5587mm
2910lbs 1320kg	3740lbs 1700kg	4000lbs 1820kg	50100lbs 2280kg	3290lbs 1495kg	9psi 0.6bar				
3420lbs 1550kg	4680lbs 2120kg	5010lbs 2270kg	6270lbs 2840kg	4120lbs 1865kg	12psi 0.8bar	<b>Number of Lugs</b>	<b>Rolling Circumference Index</b>	<b>Rims</b>	
4400lbs 2000kg	6000lbs 2725kg	6420lbs 2915kg	8040lbs 3650kg	5280lbs 2400kg	17psi 1.2bar				
5360lbs 2430kg	6950lbs 3150kg	7435lbs 3370kg	9315lbs 4220kg	6115lbs 2770kg	23psi 1.6bar				
					29psi 2.0bar	<b>Tread Depth</b>	<b>Gross Flat Plate</b>	<b>Min. Dual Spacing</b>	
					32psi 2.2bar				
					35psi 2.4bar				
					38psi 2.6bar				
					41psi 2.8bar				