



Mix and match your tire order per shipping container! Authorized distributors can mix and match any type of our Samson or Advance branded tires in one container shipment, including: MTR/Mobile Crane, Bias Truck, OTR/Logging, Industrial, Farm/Skid Steer and Solid/Giant Solid.

1441 South Main St. | North Canton, Ohio 44720  
 Phone: 330.368.4200 | Fax: 330.368.4224

**MARKETING BULLETIN**  
 Date: 12-15-2014 • MB2014054-A

**Please see below for our Advance R-1W 420/85R28 radial farm load and inflation chart:**

420/85R28 139A8 TL ADVANCE									
30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Pressure	Unloaded Overall Width	Unloaded Overall Diameter	Loaded Radius	Rolling Circumference
2470lbs 1120kg	2470lbs 1120kg	2645lbs 1200kg	3310lbs 1500kg	2175lbs 985kg	6psi 0.4bar	16.5 in 418mm	56.1 in 1425mm	25.5 in 647mm	166.9 in 4240mm
2910lbs 1320kg	2910lbs 1320kg	3115lbs 1415kg	3900lbs 1770kg	2560lbs 1160kg	9psi 0.6bar				
3420lbs 1550kg	3420lbs 1550kg	3660lbs 1660kg	4585lbs 2080kg	3010lbs 1365kg	12psi 0.8bar	Number of Lugs	Rolling Circumference Index		Rims
4400lbs 2000kg	4400lbs 2000kg	4710lbs 2140kg	5895lbs 2680kg	3870lbs 1760kg	17psi 1.2bar				
5360lbs 2430kg	5360lbs 2430kg	5735lbs 2600kg	7180lbs 3255kg	4715lbs 2140kg	23psi 1.6bar				
					29psi 2.0bar	Tread Depth	Gross Flat Plate		Min. Dual Spacing
					32psi 2.2bar				
					35psi 2.4bar				
					38psi 2.6bar				
					41psi 2.8bar				