NORTH AMERICAN
COMMERCIAL TIRE RESOURCES INC.

MIX&MATCH CONTAINERS

Mix and match your tire order per shipping container! Authorized distributors can mix and match any type of our Samson or Advance branded tires in one container shipment, including: MTR/Mobile Crane, Bias Truck, OTR/Logging, Industrial, Farm/Skid Steer and Solid/Giant Solid.

1441 South Main St. | North Canton, Ohio 44720
Phone: 330.368.4200 | Fax: 330.368.4224

MARKETING BULLETIN
Date: 12-15-2014 • MB2014055-A

Please see below for our Advance R-1W 520/85R38 radial farm load and inflation chart:

520/85R38 155A8 TL ADVANCE

30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Pressure
3860lbs	3860lbs	4130lbs	5170lbs	3395lbs	6psi
1750kg	1750kg	1870kg	2345kg	1540kg	0.4bar
4680lbs	4680lbs	5010lbs	6270lbs	4120lbs	9psi
2120kg	2120kg	2270kg	2840kg	1865kg	0.6bar
5520bs	5520bs	5905bs	7395bs	4860bs	12psi
2500kg	2500kg	2675kg	3350kg	2200kg	0.8bar
6150lbs	6150lbs	6580lbs	8240lbs	5410lbs	15psi
2800kg	2800kg	2995kg	3750kg	2465kg	1.0bar
6950lbs	**6950lbs**	**7435lbs**	**9315lbs**	**6115lbs**	**17psi**
3150kg	**3150kg**	**3370kg**	**4220kg**	**2770kg**	**1.2bar**
7850lbs	7850lbs	8340lbs	10520lbs	6910lbs	20psi
3550kg	3550kg	3800kg	4755kg	3125kg	1.4bar
8550lbs	8550lbs	9150lbs	11455bs	7525lbs	23psi
3875kg	3875kg	4145kg	5190kg	3410kg	1.6bar

Unloaded Overall Width	Unloaded Overall Diameter	Loaded Radius	Rolling Circumference
20.0in	73 in	33.2 in	216.5in
507mm	1854mm	843mm	5500mm

Number of Lugs	Rolling Circumference Index	Rims
22x2	46	DW16L, W16A, DD16, W18A, DD18

Tread Depth	Gross Flat Plate	Min. Dual Spacing
68/32nds	410 sq in	27.6 in
54mm	2644 sq cm	702mm