



Mix and match your tire order per shipping container! Authorized distributors can mix and match any type of our Samson or Advance branded tires in one container shipment, including: MTR/Mobile Crane, Bias Truck, OTR/Logging, Industrial, Farm/Skid Steer and Solid/Giant Solid.

1441 South Main St. | North Canton, Ohio 44720
 Phone: 330.368.4200 | Fax: 330.368.4224

MARKETING BULLETIN
 Date: 12-15-2014 • MB2014056-A

Please see below for our Advance R-1W 380/85R30 radial farm load and inflation chart:

380/85R30 129A8 TL ADVANCE

30 mph 50 km/h	25 mph 40 km/h	20 mph 30 km/h	6 mph 10 km/h	25 mph Dual 40 km/h Dual	Pressure	Unloaded Overall Width	Unloaded Overall Diameter	Loaded Radius	Rolling Circumference
1820lbs 825kg	1820lbs 825kg	1945lbs 885kg	2440lbs 1105kg	1600lbs 725kg	6psi 0.4bar	14.7in 374mm	56.3in 1430mm	26.6in 675mm	168.1in 4270mm
2150lbs 975kg	2150lbs 975kg	2300lbs 1045kg	2880lbs 1305kg	1890lbs 860kg	8psi 0.55bar				
2470lbs 1120kg	2470lbs 1120kg	2645lbs 1200kg	3310lbs 1500kg	2175bs 985kg	10psi 0.7bar				
2680lbs 1215kg	2680lbs 1215kg	2870lbs 1300kg	3590lbs 1630kg	2360lbs 1070kg	12psi 0.8bar	Number of Lugs 22x2	Rolling Circumference Index 41		Rims W12, W13
3000lbs 1360kg	3000lbs 1360kg	3210lbs 1455kg	4020lbs 1820kg	2640lbs 1195kg	14psi 0.95bar				
3200lbs 1450kg	3200lbs 1450kg	3425lbs 1550kg	4290lbs 1945kg	2815lbs 1275kg	16psi 1.1bar	Tread Depth 59/32nds 47 mm	Gross Flat Plate 198 sq in 1280 sq cm		Min. Dual Spacing 20.5 in 520 mm
3420lbs 1550kg	3420lbs 1550kg	3660lbs 1660kg	4585lbs 2075kg	3010lbs 1365kg	18psi 1.25bar				
3640bs 1650kg	3640bs 1650kg	3895bs 1765kg	4880bs 2210kg	3205bs 1450kg	20psi 1.4bar				
3860lbs 1750kg	3860lbs 1750kg	4130lbs 1875kg	5170lbs 2345kg	3395lbs 1540kg	22psi 1.5bar				
4080lbs 1850kg	4080lbs 1850kg	4365lbs 1980kg	5465lbs 2480kg	3590lbs 1630kg	24psi 1.65bar				