

1441 South Main St. | North Canton, Ohio 44720 Phone: 330.368.4200 | Fax: 330.368.4224

> MARKETING BULLETIN Date: 05-19-2015 • MB2015019-S

## **New Samson Farm Radial R-1W**



(in.)

58.7

77.1

96120-2

96125-2

600/65R28

710/70R38

We are pleased to announce that our Samson Farm Radial R-1W is now available in two new sizes. Orders are now being accepted.

## **Features include:**

-Bar angle provides superior traction in the field and good wear during road transportation.

6770

11700

(32nds)

64.3

73.1

W18L


DW23B

(lbs)

355

669

- -Heavy duty design for excellent ride, snag resistance and long wear.
- -Radial design construction.



Cat#	Size	Туре	Design	GTC Pattern	Ply Rating	Speed Symbol	Load Index	Section Width (in.)
96120-2	600/65R28	TBLS	Samson Farm Radial R-1W	R-1W	NA	A8	147	23.3
96125-2	710/70R38	TBLS	Samson Farm Radial R-1W	R-1W	NA	A8	166	28.2
Cat #	Size	Overall Diam.	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth	Tire Weight

23

25

25