



1441 South Main St. | North Canton, Ohio 44720
 Phone: 330.368.4200 | Fax: 330.368.4224

MARKETING BULLETIN
 Date: 07-30-2015 • MB2015031-S


New Samson Farm Radial R-1W Sizes Available



We are pleased to announce that our Samson Farm Radial R-1W is now available in three new sizes. Orders are now being accepted.

Features include:

- Bar angle provides superior traction in the field and good wear during road transportation.
- Heavy duty design for excellent ride, snag resistance and long wear.
- Radial design construction.



Cat #	Size	Type	Design	GTC Pattern	Ply Rating	Speed Symbol	Load Index	Section Width (in.)
96132-2	380/85R30	TL	Farm Radial R-1W	R-1W	na	A8	135	15.0
96135-2	480/80R38	TL	Farm Radial R-1W	R-1W	na	A8	149	18.9
96130-2	480/80R42	TL	Farm Radial R-1W	R-1W	na	A8	151	18.9

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
96132-2	380/85R30	55.4	25	23	4800	W12	59.2	208
96135-2	480/80R38	68.2	25	23	7150	W15	63.0	346
96130-2	480/80R42	72.2	25	23	7600	DW16L	65.5	399