



Mix and match your tire order per shipping container! Authorized distributors can mix and match any type of our Samson or Advance branded tires in one container shipment, including: MTR/Mobile Crane, Bias Truck, OTR/Logging, Industrial, Farm/Skid Steer and Solid/Giant Solid.

1441 South Main St. | North Canton, Ohio 44720
 Phone: 330.368.4200 | Fax: 330.368.4224

MARKETING BULLETIN
 Date: 1-08-2015 • MB201508-A

New Advance E-3/L-3 Rock Crusher



We are pleased to announce four new sizes to our line of Advance E-3/L-3 Rock Crusher tires. Orders are now being accepted!

Features Include:

- Special tread compound designed to reduce punctures and cuts.
- Strong carcass structure designed to handle the heaviest loads.
- Extra wide tread provides a greater footprint.
- Increased ply rating for those specialty applications

Cat #	Size	Type	Design	GTC Pattern	Ply Rating	Speed Symbol	Load Index	Section Width (in.)
17056G	13.00-24	TL	Rock Crusher Earthmover E-3	E-3/L-3	16	B/*A2	N/A	13.78
17057G	14.00-24	TL	Rock Crusher Earthmover E-3	E-3/L-3	16	B/*A2	N/A	14.76
17194G	20.5-25	TL	Rock Crusher Earthmover E-3	E-3/L-3	50	A2	N/A	20.50
17225G	23.5-25	TL	Rock Crusher Earthmover E-3	E-3/L-3	24	B/*A2	N/A	23.43

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
17056G	13.00-24	51.18	30/*5	55/*80	7710/*13900	10.0	35.3	209
17057G	14.00-24	53.94	30/*5	55/*80	88200/*16100	10.00	35.7	253
17194G	20.5-25	58.66	5	163	35720	17.00	40.3	651
17225G	23.5-25	63.58	30/*5	51/*69	17600/*27600	19.50	44.1	568