

Mix and match your tire order per shipping container! Authorized distributors can mix and match any type of our Samson or Advance branded tires in one container

shipment, including: MTR/Mobile Crane, Bias Truck, OTR/Logging, Industrial, Farm/Skid Steer and Solid/Giant Solid.

1441 South Main St. | North Canton, Ohio 44720 Phone: 330.368.4200 | Fax: 330.368.4224

MARKETING BULLETIN
Date: 3-30-2015 • MB201513-S

ST TRAILER TIRES TECHNICAL DATA



ST12021-2 ST225/90D16

ST12023-2 | ST225/90D16


31.8

31.8

The following ST Trailer Tires are now available. Orders are now being accepted!

Features Include:

- -Advanced tread compound increases long, even wear.
- -Enhanced groove design improves wet traction.



S3520/D3080

S4080/D3520

6.00G

6.00G

13.2

13.2

37.66

45.36

| Cat # | Size | Туре | Design | GTC Pattern | Ply Rating | Speed Symbol | Load Index | Section Width (in.) |
|-----------|-------------|---------------------------|------------------------|----------------------------|------------------|-----------------|---------------------------|---------------------------|
| ST12012-2 | ST205/90D15 | TBLS | Samson Trailer Express | RB-233 | 10 | K | N/A | 7.9 |
| ST12021-2 | ST225/90D16 | TBLS | Samson Trailer Express | RB-233A | 10 | K | N/A | 8.6 |
| ST12023-2 | ST225/90D16 | TBLS | Samson Trailer Express | RB-233A | 14 | K | N/A | 8.6 |
| | | | | | | | | |
| Cat # | Size | Overall Diam. (in.) | Max Speed | Infl. Pressure (psi) | Max. Load (lbs.) | Standard Rim | Tread Depth (32nds) | Tire Weight (lbs) |
| ST12012-2 | ST205/90D15 | 29.6 | 68 | 80 | S2910/D2540 | 5.50F | 13.9 | 30.4 |

80

105

68

68