



1441 South Main St. | North Canton, Ohio 44720  
 Phone: 330.368.4200 | Fax: 330.368.4224


**MARKETING BULLETIN**  
 Date: 01-4-2016 • MB201601-S

## New Samson Farm Radial R-1W Sizes Available

We are pleased to announce that our Samson Farm Radial R-1W is now available in new sizes. Orders are now being accepted.

**Features include:**

- Bar angle provides superior traction in the field and good wear during road transportation.
- Heavy duty design for excellent ride, snag resistance and long wear.
- Radial design construction.



Cat #	Size	Type	Design	GTC Pattern	Ply Rating	Speed Symbol	Load Index	Section Width (in.)
96155-2	380/85R28	TL	Farm Radial R-1W	R-1W	NA	A8	133	15.0
96150-2	380/85R34	TL	Farm Radial R-1W	R-1W	NA	A8	137	15.0
96158-2	460/85R38	TL	Farm Radial R-1W	R-1W	NA	A8	151	17.9
96160-2	420/90R30	TL	Farm Radial R-1W	R-1W	NA	A8	147	16.5
96152-2	380/85R24	TL	Farm Radial R-1W	R-1W	NA	A8	131	14.9
96145-2	620/70R42	TL	Farm Radial R-1W	R-1W	NA	A8	160	24.6
96162-2	340/85R24	TL	Farm Radial R-1W	R-1W	NA	A8	125	13.5
96164-2	340/85R28	TL	Farm Radial R-1W	R-1W	NA	A8	127	13.5
96166-2	480/70R30	TL	Farm Radial R-1W	R-1W	NA	A8	141	18.9
96168-2	420/70R28	TL	Farm Radial R-1W	R-1W	NA	A8	133	16.5
96170-2	420/70R24	TL	Farm Radial R-1W	R-1W	NA	A8	130	16.5

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
96155-2	380/85R28	53.4	25.0	23	4540	W12	58.0	178
96150-2	380/85R34	59.5	25.0	23	5080	W12	59.2	215
96158-2	460/85R38	68.8	25.0	23	7600	W16L	65.5	363
96160-2	420/90R30	59.8	25.0	23	6800	W13	60.5	257
96152-2	380/85R24	49.5	25.0	23	4300	W12	58.0	157
96145-2	620/70R42	76.2	25.0	23	9900	DW20A	65.5	552
96162-2	340/85R24	46.8	25.0	23	3640	W11	56.7	140
96164-2	340/85R28	50.9	25.0	23	3860	W11	56.7	159
96166-2	480/70R30	58.2	25.0	23	5680	W15L	59.2	277
96168-2	420/70R28	53.1	25.0	23	4540	W13	56.7	192
96170-2	420/70R24	49.1	25.0	23	4180	W13	56.7	171