



1441 South Main St. | North Canton, Ohio 44720
 Phone: 330.368.4200 | Fax: 330.368.4224

MARKETING BULLETIN
 Date: 01-5-2016 • MB201602-A

New Advance Radial Industrial R-4E

We are pleased to introduce our new Advance Radial Industrial R-4E. Orders are now being accepted.

Features include:

- Wide tread design to decrease soil compaction.
- Puncture resistant tread design.
- Deep tread pattern to provide additional traction.
- Wear resistant compound to prolong tire service life.



Cat #	Size	Type	Design	GTC Pattern	Ply Rating	Speed Symbol	Load Index	Section Width (in.)
96200G	17.5LR24	TBLS	Radial Industrial R-4E	R-4E	NA	B	152	17.5
96205G	19.5LR24	TBLS	Radial Industrial R-4E	R-4E	NA	B	156	19.5
96206G	19.5LR24	TBLS	Radial Industrial R-4E (Steel Belt)	R-4E	NA	B	156	19.5
96208G	540/70R24	TBLS	Radial Industrial R-4E	R-4E	NA	B	153	21.7

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
96200G	17.5LR24	49.2	31	46	7820	DW15L	45.4	197
96205G	19.5LR24	52	31	44	8820	DW17L	47.9	240
96206G	19.5LR24	52	31	44	8820	DW17L	47.9	248
96208G	540/70R24	53.8	31	35	8050	DW18L	49.8	288