



1441 South Main St. | North Canton, Ohio 44720
 Phone: 330.368.4200 | Fax: 330.368.4224

MARKETING BULLETIN
 Date: 01-5-2016 • MB201602-S

New Samson Radial Industrial R-4E

We are pleased to introduce our new Samson Radial Industrial R-4E. Orders are now being accepted.

Features include:

- Wide tread design to decrease soil compaction.
- Puncture resistant tread design.
- Deep tread pattern to provide additional traction.
- Wear resistant compound to prolong tire service life.



Cat #	Size	Type	Design	GTC Pattern	Ply Rating	Speed Symbol	Load Index	Section Width (in.)
96200-2	17.5LR24	TBLS	Radial Industrial R-4E	R-4E	NA	B	152	17.5
96205-2	19.5LR24	TBLS	Radial Industrial R-4E	R-4E	NA	B	156	19.5
96206-2	19.5LR24	TBLS	Radial Industrial R-4E (Steel Belt)	R-4E	NA	B	156	19.5
96208-2	540/70R24	TBLS	Radial Industrial R-4E	R-4E	NA	B	153	21.7

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
96200-2	17.5LR24	49.2	31	46	7820	DW15L	45.4	197
96205-2	19.5LR24	52	31	44	8820	DW17L	47.9	240
96206-2	19.5LR24	52	31	44	8820	DW17L	47.9	248
96208-2	540/70R24	53.8	31	35	8050	DW18L	49.8	288