



1441 South Main St. | North Canton, Ohio 44720  
 Phone: 330.368.4200 | Fax: 330.368.4224

**MARKETING BULLETIN**  
 Date: 03.30.2017 • MB201703-A

## New Sizes/Plies Added to Our GL286A



We are pleased to introduce 2 new sizes to our Advance GL286A Radial Truck Tire line.

**Features include:**

- Optimized profile design provides better handling characteristics.
- Enhanced tread compound provides abrasion resistance.
- Strengthened carcass design increases longer service life and improves retread-ability.
- Mid/Long Highway Service



Cat #	Size	Type	Design	GTC Pattern	PLY Rating	Speed Symbol	Load Index	Section Width (in.)
88214G	385/55R22.5	TBLS	ADVANCE RADIAL GL286A	GL286A	20	K	S160	15.2
88211G	385/65R22.5	TBLS	ADVANCE RADIAL GL286A	GL286A	20	K	S160	15.2
Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
88214G	385/55R22.5	39.2	68	130	S9920	12.25	18.3	143.88
88211G	385/65R22.5	42.2	68	130	S9920	11.75	19.3	156.77