



1441 South Main St. | North Canton, Ohio 44720
 Phone: 330.368.4200 | Fax: 330.368.4224

MARKETING BULLETIN
 Date: 04.6.2017 • MB201710-S

New Sizes/Plies Added to Our GL665A



We are pleased to introduce that 4 new sizes have been added to our Samson GL665A Radial Truck Tire line.

Features include:

- Specialized “Z” shaped grooves provide for excellent traction and braking abilities.
- Compound is specifically designed to ensure tear-resistance.
- Lug grooves located on the shoulders improve traction capability.
- Short/Mid Haul Mixed Service



Cat #	Size	Type	Design	GTC Pattern	PLY Rating	Speed Symbol	Load Index	Section Width (in.)
87021-2	11R22.5	TBLS	SAMSON RADIAL GL665A	GL665A	18	L	S148/D145	11.0
87011-2	12R24.5	TBLS	SAMSON RADIAL GL665A	GL665A	18	L	S154/D151	11.8
87025-2	12.00R24	TT	SAMSON RADIAL GL665A	GL665A	20	J	S160/D157	12.4
87019-2	275/70R22.5	TBLS	SAMSON RADIAL GL665A	GL665A	16	M	S144/D141	10.9

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
87021-2	11R22.5	41.3	75	125	S6940/D6395	8.25	21.4	115.2
87011-2	12R24.5	44.7	75	135	S8270/D7610	9.00	23.9	132.31
87025-2	12.00R24	47.9	62	130	S9920/D9090	8.50	23.9	198.66
87019-2	275/70R22.5	37.7	81	120	S6175/D5675	8.25	22	105