



1441 South Main St. | North Canton, Ohio 44720  
 Phone: 330.368.4200 | Fax: 330.368.4224

**MARKETING BULLETIN**  
 Date: 04.6.2017 • MB201711-S

## New Sizes/Plies Added to Our GL662A



We are pleased to introduce that 2 new sizes have been added to our Samson GL662A Radial Truck Tire line.

**Features include:**

- Aggressive on/off road, all position radial.
- Designed for the extra traction with cut and chip resistant compound.
- Short/Mid Haul Mixed Service



Cat #	Size	Type	Design	GTC Pattern	PLY Rating	Speed Symbol	Load Index	Section Width (in.)
88503-2	12R22.5	TBLS	SAMSON RADIAL GL662A	GL662A	18	L	S152/D148	11.8
88516-2	295/75R22.5	TBLS	SAMSON RADIAL GL662A	GL662A	16	L	S146/D143	11.7
Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
88503-2	12R22.5	42.7	75.0	125	S7830/D6940	9.00	19.9	122.5
88516-2	295/75R22.5	39.9	75.0	120	S6610/D6005	9.00	19.5	100.87