

1441 South Main St. | North Canton, Ohio 44720 Phone: 330.368.4200 | Fax: 330.368.4224

MARKETING BULLETIN Date: 04.7.2017 • MB201713-S

## **New Sizes Added to Our GL687D**



We are pleased to introduce 2 new sizes that have been added to our Samson GL687D Radial Truck Tire line.

## **Features include:**

- Thick, durable block and lug grooves provide for excellent traction.
- Designed for even distribution where the tread meets the surface.
- Tread pattern provides for slip resistance, prevents irregular wear, and improves stability.
- Short/Mid Haul Mixed Service



Cat #	Size	Туре	Design	GTC Pattern	PLY Rating	Speed Symbol	Load Index	Section Width (in.)
88358-2	13R22.5	TBLS	SAMSON RADIAL GL687D	GL687D	18	K	S154/D150	12.6
88366-2	295/80R22.5	TBLS	SAMSON RADIAL GL687D	GL687D	18	М	S152/D149	11.7
Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
88358-2	13R22.5	44.3	68.0	125	S8270/D7390	9.75	24.6	160.66
88366-3	205/80P22 5	/11 3	81 N	120	\$7830/D7160	9.00	25.8	13/1 25