



1441 South Main St. | North Canton, Ohio 44720  
 Phone: 330.368.4200 | Fax: 330.368.4224

**MARKETING BULLETIN**  
 Date: 04.20.2017 • MB201719-S

## New Samson Radial GL289A



We are pleased to introduce our Samson GL289A Radial Truck Tire.

### Features include:

- Beefy, buttressed shoulders help resist tearing and accelerated wear in high scrub applications.
- Extra strong sidewalls to help protect against most impacts and abrasions for long casing life.
- Tapered grooves help deliver additional defense against stone drilling.
- High scrub compound (chip and cut resistant) make the GL289A our longest wear regional steer tire.



Cat #	Size	Type	Design	GTC Pattern	PLY Rating	Speed Symbol	Load Index	Section Width (in.)
289003S	10R22.5	TBLS	SAMSON RADIAL GL289A	GL289A	16	L	S144/D142	10.0
289001S	11R22.5	TBLS	SAMSON RADIAL GL289A	GL289A	16	M	S146/D143	11.0
289002S	11R24.5	TBLS	SAMSON RADIAL GL289A	GL289A	16	L	S149/D146	11.0
289004S	275/80R22.5	TBLS	SAMSON RADIAL GL289A	GL289A	16	M	S147/D144	10.9
289005S	285/75R24.5	TBLS	SAMSON RADIAL GL289A	GL289A	16	L	S147/D144	11.1

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
289003S	10R22.5	40.2	75	130	S6175/D5840	7.50	19.5	99.88
289001S	11R22.5	41.3	81	120	S6610/D6005	8.25	22.7	118.39
289002S	11R24.5	43.5	75	120	S7160/D6610	8.25	22.7	124.07
289004S	275/80R22.5	39.8	81	120	S6780/D6175	8.25	22.7	103.47
289005S	285/75R24.5	41.3	75	120	S6780/D6175	8.25	22.7	112.53