



1441 South Main St. | North Canton, Ohio 44720
 Phone: 330.368.4200 | Fax: 330.368.4224

MARKETING BULLETIN
 Date: 07-10-2014 • MB2014025-S

New SmartWay Approved GL185T!



Features and Benefits:

12/32" tread depth minimizes tread squirm and irregular wear

Innovative groove technology to minimize stone retention, extending casing life and improved retreadability.

Durable casing provides long original tread life and promotes multiple retreads

Technologically advanced tread compounds provides low rolling resistance, promoting greater fuel economy and increased mileage.



Cat #	Size	Type	Design	GTC Pattern	Ply Rating	Speed Symbol	Load Index	Section Width (in.)
86620-2	11R22.5	TL	Samson Radial Truck GL185T	GL185T LET	14	M	S144/D142	11.0
86622-2	11R22.5	TL	Samson Radial Truck GL185T	GL185T LET	16	M	S146/D143	11.0
86624-2	11R24.5	TL	Samson Radial Truck GL185T	GL185T LET	14	M	S146/D143	11.0
86626-2	11R24.5	TL	Samson Radial Truck GL185T	GL185T LET	16	L	S149/D146	11.0
86632-2	285/75R24.5	TL	Samson Radial Truck GL185T	GL185T LET	14	M	S144/D141	11.1
86634-2	285/75R24.5	TL	Samson Radial Truck GL185T	GL185T LET	16	L	S147/D144	11.1
86628-2	295/75R22.5	TL	Samson Radial Truck GL185T	GL185T LET	14	M	S144/D141	11.7
86630-2	295/75R22.5	TL	Samson Radial Truck GL185T	GL185T LET	16	L	S146/D143	11.7

Cat #	Size	Overall Diam. (in.)	Max Speed	Infl. Pressure (psi)	Max. Load (lbs.)	Standard Rim	Tread Depth (32nds)	Tire Weight (lbs)
86620-2	11R22.5	41.5	81	105	S6175/D5840	8.25	12.0	102
86622-2	11R22.5	41.5	81	120	S6610/D6005	8.25	12.0	102
86624-2	11R24.5	43.5	81	105	S6610/D6005	8.25	12.0	109
86626-2	11R24.5	43.5	75	120	S7160/D6610	8.25	12.0	109
86632-2	285/75R24.5	41.3	81	110	S6175/D5675	8.25	12.0	100
86634-2	285/75R24.5	41.3	75	120	S6780/D6175	8.25	12.0	100
86628-2	295/75R22.5	39.9	81	110	S6175/D5675	9.00	12.0	98.0
86630-2	295/75R22.5	39.9	75.0	120	S6610/D6005	9.00	12.0	100