



1441 South Main Street • North Canton, Ohio 44720

Phone: 330.368.4200 • Fax: 330.368.4224

MARKETING BULLETIN
Date: 3.30.2022 • MB2022-08-A

New Sizes added to our Farm R1W Radial Rear Line



We are pleased to introduce 10 new sizes that have been added to our Advance R1W Radial Rear Farm Tire Line.

Features include:

- 45° bar angle and deep bars that provide superior traction in the field.
- Heavy duty design for snag resistance and long wear.
- Flexible sidewall creates large square footprint which decreases soil compaction.

SKU #	Size/Ply	Type	Design/Pattern	Speed Symbol	Max Speed	Load Index	Max Load (lbs.)	Section Width (in.)	Overall Dia. (in.)	Inflation Pressure (psi)	Tread Depth (32nds)	Tire Weight (lbs.)
96400G	280/70R18	TBLS	Advance R1W	D	40	114	2600	11.1	33.4	35	46.6	67
96402G	280/70R20	TBLS	Advance R1W	D	40	116	2760	11.1	35.4	35	46.6	72
96404G	320/70R20	TBLS	Advance R1W	D	40	113	2540	12.5	38.6	23	48.5	85
96406G	360/70R20	TBLS	Advance R1W	D	40	129	4080	14.0	41.0	35	49.1	109
96139G	620/75R34	TBLS	Advance R1W	A8	25	170	13200	24.6	70.6	46	60.4	559
96179G	460/85R34	TBLS	Advance R1W	A8/B	25	147	6800	17.9	64.8	23	65.5	344
96193G	IF580/80R34	TBLS	Advance R1W	A8	25	177	16100	22.6	70.5	52	69.2	538
96198G	IF520/85R42	TBLS	Advance R1W	A8	25	169	12800	20.7	76.8	35	68.0	525
96149G	480/65R28	TBLS	Advance R1W	D	40	142	5840	18.9	52.6	35	61.7	251
96408G	750/65R26CFO	TBLS	Advance R1W	D	40	171	13530	29.7	64.4	46	70.6	590