



1441 South Main Street • North Canton, Ohio 44720

Phone: 330.368.4200 • Fax: 330.368.4224

**MARKETING BULLETIN**  
Date: 3.30.2022 • MB2022-08-S

## New Sizes added to our Farm R1W Radial Rear Line



We are pleased to introduce 10 new sizes that have been added to our Samson R1W Radial Rear Farm Tire Line.

Features include:

- 45° bar angle and deep bars that provide superior traction in the field.
- Heavy duty design for snag resistance and long wear.
- Flexible sidewall creates large square footprint which decreases soil compaction.

SKU #	Size/Ply	Type	Design/Pattern	Speed Symbol	Max Speed	Load Index	Max Load (lbs.)	Section Width (in.)	Overall Dia. (in.)	Inflation Pressure (psi)	Tread Depth (32nds)	Tire Weight (lbs.)
96400-2	280/70R18	TBLS	Samson R1W	D	40	114	2600	11.1	33.4	35	46.6	67
96402-2	280/70R20	TBLS	Samson R1W	D	40	116	2760	11.1	35.4	35	46.6	72
96404-2	320/70R20	TBLS	Samson R1W	D	40	113	2540	12.5	38.6	23	48.5	85
96406-2	360/70R20	TBLS	Samson R1W	D	40	129	4080	14.0	41.0	35	49.1	109
96139-2	620/75R34	TBLS	Samson R1W	A8	25	170	13200	24.6	70.6	46	60.4	559
96179-2	460/85R34	TBLS	Samson R1W	A8/B	25	147	6800	17.9	64.8	23	65.5	344
96193-2	IF580/80R34	TBLS	Samson R1W	A8	25	177	16100	22.6	70.5	52	69.2	538
96198-2	IF520/85R42	TBLS	Samson R1W	A8	25	169	12800	20.7	76.8	35	68.0	525
96149-2	480/65R28	TBLS	Samson R1W	D	40	142	5840	18.9	52.6	35	61.7	251
96408-2	750/65R26CFO	TBLS	Samson R1W	D	40	171	13530	29.7	64.4	46	70.6	590